

OIL ANALYSIS REPORT

Marcus Hook/Cryogenic/Compressor **CRYOGENIC COMPRESSOR 50-C-201C** Component

Rotary Compressor SHELL TELLUS S4 VX 32 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





SAMPLE INFORMATION method TO60001821 TO90003049 TO90002749 Sample Number **Client Info** 25 Apr 2023 02 Nov 2022 Sample Date Client Info 05 Nov 2023 Client Info 0 0 0 Machine Age hrs Oil Age hrs Client Info n 0 0 Oil Changed Client Info N/A N/A N/A NORMAL Sample Status NORMAL NORMAL WEAR METALS >70 0 0 0 Iron ppm ASTM D5185m Chromium ASTM D5185m 0 0 0 ppm >10 Nickel ppm ASTM D5185m 0 0 0 Titanium ASTM D5185m 0 0 0 ppm 0 Silver ppm ASTM D5185m 0 0 Aluminum ASTM D5185m >3 0 0 ppm <1 Lead ASTM D5185m >4 0 0 0 ppm ASTM D5185m 0 0 >20 Copper ppm <1 Tin ppm ASTM D5185m >3 0 0 0 Vanadium ASTM D5185m 0 0 0 ppm Cadmium ppm ASTM D5185m 0 0 0 0 0 0 Boron ppm ASTM D5185m Barium ppm ASTM D5185m 0 0 0 0 0 0 Molybdenum ppm ASTM D5185m 0 0 0 Manganese ppm ASTM D5185m 0 ASTM D5185m 0 Magnesium ppm <1 3 0 0 Calcium ppm ASTM D5185m 20 Phosphorus ppm ASTM D5185m 42 40 Zinc ASTM D5185m 0 0 0 ppm 0 Sulfur ASTM D5185m 0 0 ppm CONTAMINANTS Silicon ppm ASTM D5185m >45 0 0 <1 0 Sodium ppm ASTM D5185m <1 <1 Potassium ASTM D5185m >20 0 0 <1 ppm 0.004 0.003 Water % ASTM D6304 >0.6 0.475 40.0 30.4 ppm Water ppm **ASTM D6304** 4750 FLUID CLEANLINESS >2500 396 Particles >4µm ASTM D7647 1331 1164 >320 317 93 Particles >6µm ASTM D7647 136

Particles >14µm

Particles >21µm

Particles >38µm

Particles >71µm

Oil Cleanliness

Acid Number (AN)

FLUID DEGRADATION

ASTM D7647

ASTM D7647

ASTM D7647

ISO 4406 (c)

ASTM D8045

mg KOH/g

ASTM D7647 >20

>80

>4

>3

>18/15/13

13

3

0

0

18/15/11

0.068

8

2

0

0

16/14/10

0.058

19

9

0


0


17/14/11


0.072



OIL ANALYSIS REPORT








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.6	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	33.8	32.2	32.0	32.66
Visc @ 100°C	cSt	ASTM D445	9.93	6.2	6.3	6.02
Viscosity Index (VI)	Scale	ASTM D2270	300	144	151	132
SAMPLE IMAGES	3	method	limit/base	current	history1	history2
Color				p 204 C		50 C 20

Bottom

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)



Report Id: ETCMHOOK [WUSCAR] 05999965 (Generated: 11/08/2023 13:45:54) Rev: 1

Certificate L2367

Submitted By: ERIC THORNTON

Page 2 of 2

T:

F: