


# PROBLEM SUMMARY


Sample Rating Trend



Machine Id  
**KAESER BSD50 6948677 (S/N 2136)**  
Component  
**Compressor**  
Fluid  
**KAESER SIGMA (OEM) S-460 (--- QTS)**

## COMPONENT CONDITION SUMMARY

▲ Particle Trend



## RECOMMENDATION

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

## PROBLEMATIC TEST RESULTS

Sample Status			ABNORMAL	ATTENTION	ABNORMAL
Particles >6µm	ASTM D7647	>1300	▲ <b>30123</b>	▲ 1438	---
Particles >14µm	ASTM D7647	>80	▲ <b>2343</b>	67	---
Particles >21µm	ASTM D7647	>20	▲ <b>745</b>	16	---
Particles >38µm	ASTM D7647	>4	▲ <b>24</b>	0	---
Oil Cleanliness	ISO 4406 (c)	>--/17/13	▲ <b>24/22/18</b>	▲ 21/18/13	---

Customer Id: ALESEB  
Sample No.: KC06000551  
Lab Number: 06000551  
Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data:  
Jonathan Hester +1 919-379-4092 x4092  
[jhester@wearcheckusa.com](mailto:jhester@wearcheckusa.com)

To change component or sample information:  
Customer Service +1 1-800-237-1369  
[customerservice@wearcheck.com](mailto:customerservice@wearcheck.com)

## RECOMMENDED ACTIONS

*There are no recommended actions for this sample.*

## HISTORICAL DIAGNOSIS

### 13 Apr 2023 Diag: Don Baldrige

ISO



Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor. All component wear rates are normal. There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

view report



### 04 Jun 2022 Diag: Don Baldrige

WEAR




We recommend you service the filters on this component. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample. The chromium level is abnormal. All other component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

view report



# OIL ANALYSIS REPORT

Sample Rating Trend



ISO



Machine Id  
**KAESER BSD50 6948677 (S/N 2136)**

Component

**Compressor**

Fluid

**KAESER SIGMA (OEM) S-460 (--- QTS)**

**DIAGNOSIS**

**▲ Recommendation**

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

**Wear**

All component wear rates are normal.

**▲ Contamination**

There is a high amount of particulates present in the oil.

**Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>KC06000551</b>	KC101784	KC91202
Sample Date	Client Info			<b>19 Oct 2023</b>	13 Apr 2023	04 Jun 2022
Machine Age	hrs	Client Info		<b>28312</b>	25583	18586
Oil Age	hrs	Client Info		<b>0</b>	7000	1100
Oil Changed	Client Info			<b>N/A</b>	Changed	Not Changed
Sample Status				<b>ABNORMAL</b>	ATTENTION	ABNORMAL

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<b>0</b>	0	26
Chromium	ppm	ASTM D5185m	>10	<b>0</b>	0	▲ 11
Nickel	ppm	ASTM D5185m	>3	<b>1</b>	0	0
Titanium	ppm	ASTM D5185m	>3	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>10	<b>&lt;1</b>	<1	6
Lead	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	<1
Copper	ppm	ASTM D5185m	>50	<b>8</b>	2	<1
Tin	ppm	ASTM D5185m	>10	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0






ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<b>0</b>	0	0
Barium	ppm	ASTM D5185m	90	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m		<b>0</b>	0	0
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	0	2
Magnesium	ppm	ASTM D5185m	90	<b>12</b>	0	6
Calcium	ppm	ASTM D5185m	2	<b>&lt;1</b>	0	10
Phosphorus	ppm	ASTM D5185m		<b>20</b>	169	493
Zinc	ppm	ASTM D5185m		<b>0</b>	0	0

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>0</b>	0	13
Sodium	ppm	ASTM D5185m		<b>5</b>	0	0
Potassium	ppm	ASTM D5185m	>20	<b>1</b>	0	1
Water	%	ASTM D6304	>0.05	<b>0.016</b>	0.007	0.013
ppm Water	ppm	ASTM D6304	>500	<b>161.0</b>	74.9	138.5

FLUID CLEANLINESS		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		<b>95370</b>	12625	---
Particles >6µm		ASTM D7647	>1300	▲ <b>30123</b>	▲ 1438	---
Particles >14µm		ASTM D7647	>80	▲ <b>2343</b>	67	---
Particles >21µm		ASTM D7647	>20	▲ <b>745</b>	16	---
Particles >38µm		ASTM D7647	>4	▲ <b>24</b>	0	---
Particles >71µm		ASTM D7647	>3	<b>1</b>	0	---
Oil Cleanliness		ISO 4406 (c)	>--/17/13	▲ <b>24/22/18</b>	▲ 21/18/13	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	<b>0.37</b>	0.33	0.09

# OIL ANALYSIS REPORT








PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	▲ MODER
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	45.1	45.9

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : KC06000551  
**Lab Number** : 06000551  
**Unique Number** : 10728911  
**Test Package** : IND 2

**Received** : 07 Nov 2023  
**Diagnosed** : 09 Nov 2023  
**Diagnostician** : Jonathan Hester

**FOUNDRY SAND SERVICE LLC**  
 20455 LAKE PARK BLVD  
 SEBRING, OH  
 US 44672  
 Contact: SERVICE MANAGER

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: