


OIL ANALYSIS REPORT

Sample Rating Trend





L20705
Component

Compressor

DEKKER V MAX (15 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


Jud017 Novd019 Aprd020 Novd020 Jud021 Mard022 Mard023 Osc0023								
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2		
Sample Number		Client Info		WC0843073	WC0806244	WC0774647		
Sample Date		Client Info		24 Oct 2023	17 Jul 2023	15 Mar 2023		
Machine Age	hrs	Client Info		4338	3334	2067		
Oil Age	hrs	Client Info		0	4198	2067		
Oil Changed		Client Info		Changed	Filtered	Not Changd		
Sample Status				NORMAL	NORMAL	NORMAL		
WEAR METALS		method	limit/base	current	history1	history2		
Iron	ppm	ASTM D5185m	>50	0	0	<1		
Chromium	ppm	ASTM D5185m	>10	0	0	0		
Nickel	ppm	ASTM D5185m		0	0	0		
Titanium	ppm	ASTM D5185m		0	0	0		
Silver	ppm	ASTM D5185m		0	0	0		
Aluminum	ppm	ASTM D5185m	>25	0	0	0		
Lead	ppm	ASTM D5185m	>25	0	0	0		
Copper	ppm	ASTM D5185m	>50	0	<1	0		
Tin	ppm	ASTM D5185m	>15	0	0	0		
Vanadium	ppm	ASTM D5185m		0	<1	0		
Cadmium	ppm	ASTM D5185m		0	0	0		
ADDITIVES		method	limit/base	current	history1	history2		
Boron	ppm	ASTM D5185m		0	0	0		
Barium	ppm	ASTM D5185m		0	0	0		
Molybdenum	ppm	ASTM D5185m		0	0	<1		
Manganese	ppm	ASTM D5185m		0	<1	0		
Magnesium	ppm	ASTM D5185m		0	0	2		
Calcium	ppm	ASTM D5185m		2	<1	7		
Phosphorus	ppm	ASTM D5185m		2	6	12		
Zinc	ppm	ASTM D5185m		4	0	8		
Sulfur	ppm	ASTM D5185m		148	187	169		
CONTAMINANTS		method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>25	4	7	6		
Sodium	ppm	ASTM D5185m		7	7	7		
Potassium	ppm	ASTM D5185m	>20	0	0	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2		
Acid Number (AN)	mg KOH/g	ASTM D8045		0.086	0.083	0.046		
VISUAL		method	limit/base	current	history1	history2		
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE	LIGHT	MODER		
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG		
Free Water	scalar	*Visual		NEG	NEG	NEG		




45 CSt (40°C)


30 25 20


OIL ANALYSIS REPORT







FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		26.3	26.3	25.82
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				no image		
Bottom				no image		











Certificate L2367

Laboratory Sample No. Lab Number Unique Number

: 10728991

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC0843073 : 06000631

Received Diagnosed

: 07 Nov 2023 : 09 Nov 2023

Diagnostician : Jonathan Hester Test Package : IND 2 (Additional Tests: KF)

US 55976 Contact: DICK BROADWATER dick.broadwater@halconfurniture.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (507)533-9113 F:

HALCON CORP

1811 2ND AVE NW

STEWARTVILLE, MN

Report Id: HALSTE [WUSCAR] 06000631 (Generated: 11/13/2023 15:16:06) Rev: 1

Contact/Location: DICK BROADWATER - HALSTE