

PROBLEM SUMMARY



Port Main Engine Fluid CHEVRON DELO 710 LE (250 GAL)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS								
Sample Status				ATTENTION	ABNORMAL	ABNORMAL		
Sodium	ppm	ASTM D5185m	>75	<u> </u>	<u> </u>	1 96		

Customer Id: INGPAD Sample No.: MW0058716 Lab Number: 06001139 Test Package: MAR 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Jonathan Hester +1 919-379-4092 x4092 jhester@wearcheckusa.com

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>



There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS

01 Oct 2023 Diag: Don Baldridge

DIRT



We advise that you check for possible coolant leak. We recommend an early resample to monitor this condition.All component wear rates are normal. Sodium and/or potassium levels are high. Elemental level of sodium (Na) and/or boron (B) indicates a possible cooling water leak. Elemental level of silicon (Si) above normal indicating ingress of seal material. The BN result indicates that there is suitable alkalinity remaining in the oil.

01 Sep 2023 Diag: Jonathan Hester

DIRT

We advise that you check for possible coolant leak. We recommend an early resample to monitor this condition.All component wear rates are normal. Sodium and/or potassium levels are high. Elemental level of sodium (Na) and/or boron (B) indicates a possible cooling water leak. Elemental level of silicon (Si) above normal indicating

ingress of seal material. The BN result indicates that there is suitable alkalinity remaining in the oil.



view repor



01 Aug 2023 Diag: Sean Felton

of Aug 2020 Blugt Court

We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. Resample at the next service interval to monitor.All component wear rates are normal. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.







OIL ANALYSIS REPORT

GALE C Machine Id [GALE C] 001 550006-1

Port Main Engine

CHEVRON DELO 710 LE (250 GAL)

DIAGNOSIS

A Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Sodium and/or potassium levels remain high. Test for glycol is negative.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		MW0058716	MW0058602	MW0038475
Sample Date		Client Info		01 Nov 2023	01 Oct 2023	01 Sep 2023
Machine Age	hrs	Client Info		9664	8932	8204
Oil Age	hrs	Client Info		9664	8932	8204
Oil Changed		Client Info		N/A	N/A	Not Changd
Sample Status				ATTENTION	ABNORMAL	ABNORMAL
CONTAMINATION	N	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>75	12	16	17
Chromium	ppm	ASTM D5185m	>8	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	<1	<1	<1
Titanium	ppm	ASTM D5185m	>3	0	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	2	0	2
Lead	ppm	ASTM D5185m	>18	7	8	6
Copper	ppm	ASTM D5185m	>80	11	14	11
Tin	ppm	ASTM D5185m	>14	5	5	5
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		71	70	60
Barium	ppm	ASTM D5185m		0	1	<1
Molybdenum	ppm	ASTM D5185m		44	44	45
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		29	10	12
Calcium	ppm	ASTM D5185m		3344	3140	3327
Phosphorus	ppm	ASTM D5185m		8	7	8
Zinc	ppm	ASTM D5185m	10	14	4	7
Sulfur	ppm	ASTM D5185m		2332	2400	2484
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	17	A 32	<u> </u>
Sodium	ppm	ASTM D5185m	>75	<u> </u>	2 48	1 96
Potassium	ppm	ASTM D5185m	>20	2	4	3
Glycol	%	*ASTM D2982		NEG	NEG	NEG
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.2	0.2	0.2
Nitration	Abs/cm	*ASTM D7624	>20	8.7	9.1	8.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.3	17.4	16.6
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	9.6	9.4	8.6
Base Number (BN)	ma KOH/a	ASTM D2896	9.2	10.41	9.36	9.80



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
	IES	method	limit/base	ourrent	history1	history?
I LOID I HOI LITI		methou	iiiiii/base	current	Thistory I	TIStory2
Visc @ 100°C	cSt	ASTM D445	15.5	15.1	15.1	15.0
СПАРИС						



Non-ferrous Metals

3!

30



* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (615)695-3697



Report Id: INGPAD [WUSCAR] 06001139 (Generated: 11/10/2023 08:43:21) Rev: 1