

TODAYS CAR WASH 6 - 31ST ST BLDA A TEMPLE Machine Id 6-4-PP

Component 4 Hydraulic Power Pack Fluid AW HYDRAULIC OIL ISO 32 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.







SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0877676		
Sample Date		Client Info		08 Nov 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0		
Chromium	ppm	ASTM D5185m	>20	0		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	0		
Lead	ppm	ASTM D5185m	>20	<1		
Copper	ppm	ASTM D5185m	>20	0		
Tin	ppm	ASTM D5185m	>20	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	0		
Barium	ppm	ASTM D5185m	5	0		
Molybdenum	ppm	ASTM D5185m	5	0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m	25	<1		
Calcium	ppm	ASTM D5185m	200	35		
Phosphorus	ppm	ASTM D5185m	300	242		
Zinc	ppm	ASTM D5185m	370	301		
Sulfur	ppm	ASTM D5185m	2500	812		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	6		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	1891		
Particles >6µm		ASTM D7647	>1300	396		
Particles >14µm		ASTM D7647	>160	30		
Particles >21µm		ASTM D7647	>40	9		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	18/16/12		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.57	0.30		


NORMAL




OIL ANALYSIS REPORT









Laboratory Sample No. Lab Number Unique Number Test Package	: WearCheck USA - 5 : WC0877676 I : 06006290 I	Received Diagnose	: 13	ry, NC 275 Nov 2023 Nov 2023	13	514 S FT H	'S CAR WAS IOOD STREE KILLEEN, T IS 76549-628
0.02) 400	5 35 3 30 Abnormal 25 Eggog			Nov6/23	.40		
, L	40 5 35			ig KOH/g)	.00 Abnomal		
	Viscosity @ 40°C			Nav8/23	Acid Number	14µ 21µ	38µ 71µ
	2				8		-10
	s copper lead			number of	30-		+14
	Non-ferrous Metal	s		N des (p	480		-10 -18 -16 -14
	2 0 EZ			7,	680 Abnormal		+2:
	8 6 4			122.	880 - Severe		-24
	GRAPHS Ferrous Alloys			491,	Particle Count		-72
	Bottom					no image	no image
 Nov8/23	Color					no image	no image
	Visc @ 40°C SAMPLE IMAGES		ASTM D445 method	32 limit/base	30.2 current	history1	history2
	FLUID PROPERT		method	limit/base		history1	history2
 	Free Water		*Visual	>0.05	NEG		
Mov	Odor Emulsified Water		*Visual *Visual	NORML >0.05	NORML NEG		
 Nov8/23	Sand/Dirt Appearance		*Visual *Visual	NONE NORML	NONE NORML		
	Debris	scalar	*Visual	NONE	NONE		
	Precipitate Silt		*Visual *Visual	NONE NONE	NONE		
 	Yellow Metal		*Visual	NONE	NONE		
	VISUAL White Metal	scalar	method *Visual	limit/base	e current	history1	history2

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: TODKIL [WUSCAR] 06006290 (Generated: 11/16/2023 04:40:52) Rev: 1

Contact/Location: HOWARD SCHULTZ - TODKIL

F: