

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 2327852 (S/N 1014) Component

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		KCPA009259	KCP49711	KCP42728	
Sample Date		Client Info		06 Nov 2023	14 Jul 2022	26 Jul 2021	
Machine Age	hrs	Client Info		71413	66945	63481	
Oil Age	hrs	Client Info		0	5500	1637	
Oil Changed		Client Info		N/A	Changed	Changed	
Sample Status				NORMAL	NORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>50	0	2	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	0	
Aluminum	ppm	ASTM D5185m	>10	0	<1	<1	
Lead	ppm	ASTM D5185m	>10	0	0	0	
Copper	ppm	ASTM D5185m	>50	<1	7	1	
Tin	ppm	ASTM D5185m	>10	0	<1	0	
Antimony	ppm	ASTM D5185m				0	
Vanadium	ppm	ASTM D5185m		0	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	0	0	2	6	
Barium	ppm	ASTM D5185m	90	55	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	0	0	
Manganese	ppm	ASTM D5185m		0	<1	0	
Magnesium	ppm	ASTM D5185m	100	76	27	2	
Calcium	ppm	ASTM D5185m	0	0	0	0	
Phosphorus	ppm	ASTM D5185m	0	<1	85	356	
Zinc	ppm	ASTM D5185m	0	0	30	3	
Sulfur	ppm	ASTM D5185m	23500	18380	21895	5026	
CONTAMINANTS		method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	0	2	0	
Sodium	ppm	ASTM D5185m		6	6	<1	
Potassium	ppm	ASTM D5185m	>20	0	1	0	
Water	%	ASTM D6304	>0.05	0.019	0.017	0.006	
ppm Water	ppm	ASTM D6304	>500	190.7	178.6	61.8	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2	
Particles >4µm		ASTM D7647		3141	829	24095	
Particles >6µm		ASTM D7647	>1300	366	120	6 315	
Particles >14µm		ASTM D7647	>80	21	9	A 315	
Particles >21µm		ASTM D7647	>20	6	4	6 1	
Particles >38µm		ASTM D7647	>4	0	0	0	
Particles >71µm		ASTM D7647	>3	0	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/16/12	17/14/10	▲ 20/15	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2	
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.34	0.29	0.139	
0:10:53) Rev: 1				Contact/Location: TYLER ? - 360WOO			

Report Id: 360WOO [WUSCAR] 06006345 (Generated: 11/15/2023 10:10:53) Rev: 1

Dece 1



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	45	44.3	44.2	44.5
SAMPLE IMAGES	;	method	limit/base	current	history1	history2
Color						

Bottom



Contact/Location: TYLER ? - 360WOO