



# 1300 CPR 003

Component Compressor Fluid GARDNER DENVER AEON 9000 SP (30 GAL)

## COMPONENT CONDITION SUMMARY



## RECOMMENDATION

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.

## PROBLEMATIC TEST RESULTS

PROBLEMATIC TEST RESULTS							
Sample Status				ABNORMAL	NORMAL	NORMAL	
Water	%	ASTM D6304	>0.1	<u> </u>			
ppm Water	ppm	ASTM D6304	>1000	<u> </u>			
Particles >4µm		ASTM D7647	>10000	<u> </u>	1964	467	
Particles >6µm		ASTM D7647	>2500	🔺 18796	619	122	
Particles >14µm		ASTM D7647	>320	<u> </u>	41	14	
Particles >21µm		ASTM D7647	>80	<u> </u>	7	4	
Oil Cleanliness		ISO 4406 (c)	>20/18/15	<b>A</b> 23/21/17	18/16/13	16/14/11	

PrtFilter

Customer Id: APCFRA Sample No.: PH0001953 Lab Number: 06007631 Test Package: PLANT



To manage this report scan the QR code

*To discuss the diagnosis or test data:* Doug Bogart +1 (800)237-1369 x4016 <u>dougb@wearcheckusa.com</u>

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

## **RECOMMENDED ACTIONS**

There are no recommended actions for this sample.

## HISTORICAL DIAGNOSIS

### 24 Sep 2023 Diag: Doug Bogart



Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

# view report

view report

#### 22 Jul 2023 Diag: Jonathan Hester



 $\checkmark$ 

Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

.....





## 03 Jun 2023 Diag: Doug Bogart

We recommend you service the filters on this component. Resample at the next service interval to monitor.All component wear rates are normal. There is a light concentration of water present in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





## **OIL ANALYSIS REPORT**





Machine Id

## 1300 CPR 003

Component Compressor

Fluid

## GARDNER DENVER AEON 9000 SP (30 GAL)

## DIAGNOSIS

## Recommendation

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.

## Wear

All component wear rates are normal.

## Contamination

There is a high amount of particulates present in the oil. There is a light concentration of water present in the oil.

## Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.





SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PH0001953	PH0001935	PH0001147
Sample Date		Client Info		29 Oct 2023	24 Sep 2023	22 Jul 2023
Machine Age	hrs	Client Info		51291	0	49183
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	N/A	N/A
Sample Status				ABNORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	maa	ASTM D5185m	>10	0	0	0
Nickel	maa	ASTM D5185m		0	0	0
Titanium	maa	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	0	0	0
Lead	ppm	ASTM D5185m	>25	<1	0	0
Copper	ppm	ASTM D5185m	>50	0	1	0
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	<1	0	0
Barium	ppm	ASTM D5185m	0	1	0	0
Molybdenum	ppm	ASTM D5185m	0	0	<1	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m	0	<1	1	3
Calcium	ppm	ASTM D5185m	0	<1	<1	0
Phosphorus	ppm	ASTM D5185m	800	799	793	743
Zinc	ppm	ASTM D5185m	0	1	0	0
Sulfur	ppm	ASTM D5185m	0	0	0	0
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	2	1
Sodium	ppm	ASTM D5185m		<1	3	<1
Potassium	ppm	ASTM D5185m	>20	0	1	<1
Water	%	ASTM D6304	>0.1	<b>A</b> 0.112		
ppm Water	ppm	ASTM D6304	>1000	<b>1120</b>		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<u> </u>	1964	467
Particles >6µm		ASTM D7647	>2500	<u> </u>	619	122
Particles >14µm		ASTM D7647	>320	<u> </u>	41	14
Particles >21µm		ASTM D7647	>80	<u> </u>	7	4
Particles >38µm		ASTM D7647	>20	13	0	0
Particles >71µm		ASTM D7647	>4	1	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	<b>A</b> 23/21/17	18/16/13	16/14/11
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	.170	0.46	0.50	0.47



# **OIL ANALYSIS REPORT**



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	0.2%	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	49.01	48.9	51.2	50.4
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color						







Bottom

PrtFilter

Contact/Location: R Filipovic - APCFRA

0ct29/23

Т:

F: