


# **OIL ANALYSIS REPORT**

## Sample Rating Trend







# MRC-295

Component

Compressor

NOT GIVEN (--- GAL)

### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jul202	3 Aug2023	Sep2023 N	ov2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60001722	TO60001470	TO60001207
Sample Date		Client Info		04 Nov 2023	06 Sep 2023	17 Aug 2023
Machine Age	hrs	Client Info		6430	6018	5846
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	<1	0	0
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>50	<1	<1	<1
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		94	124	121
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	<1
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m		8	12	8
Calcium	ppm	ASTM D5185m		1291	1287	1300
Phosphorus	ppm	ASTM D5185m		303	267	268
Zinc	ppm	ASTM D5185m		328	284	275
Sulfur	ppm	ASTM D5185m		1516	1123	1098
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	2	<1
Sodium	ppm	ASTM D5185m		2	2	2
Potassium	ppm	ASTM D5185m	>20	1	1	0
Water	%	ASTM D6304	>0.1	0.021	0.037	0.030
ppm Water	ppm	ASTM D6304	>1000	219.2	374.2	300.8
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>10000	3258	850	2423
Particles >6µm		ASTM D7647	>2500	998	170	684
Particles >14µm		ASTM D7647	>320	62	16	85
Particles >21µm		ASTM D7647	>80	10	6	30
Particles >38µm		ASTM D7647	>20	1	1	2
Particles >71µm		ASTM D7647	>4	1	1	1
Oil Cleanliness		ISO 4406 (c)	>20/18/15	19/17/13	17/15/11	18/17/14
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.60	0.74	0.47



## **OIL ANALYSIS REPORT**

