


OIL ANALYSIS REPORT

Sample Rating Trend







MRC-320

Component

Compressor

NOT GIVEN (--- GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jui2023	Aug2023	Sep2023 Oct2023	Nov2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60001729	TO60001656	TO60001425
Sample Date		Client Info		04 Nov 2023	12 Oct 2023	05 Sep 2023
Machine Age	hrs	Client Info		4684	4304	2915
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m		0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>25	<1	<1	0
Lead	ppm	ASTM D5185m	>25	<1	0	0
Copper	ppm	ASTM D5185m	>50	<1	0	0
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		97	84	127
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	<1
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m		10	16	27
Calcium	ppm	ASTM D5185m		1279	1237	1341
Phosphorus	ppm	ASTM D5185m		315	298	292
Zinc	ppm	ASTM D5185m		336	327	317
Sulfur	ppm	ASTM D5185m		2610	2227	1230
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	4	3	2
Sodium	ppm	ASTM D5185m		3	2	2
Potassium	ppm	ASTM D5185m	>20	1	2	<1
Water	%	ASTM D6304	>0.1	0.019	0.010	0.036
ppm Water	ppm	ASTM D6304	>1000	199.0	102.7	366.6
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	5522	3056	1658
Particles >6µm		ASTM D7647	>2500	1413	635	304
Particles >14µm		ASTM D7647	>320	53	18	22
Particles >21µm		ASTM D7647	>80	10	4	5
Particles >38µm		ASTM D7647	>20	1	0	0
Particles >71µm		ASTM D7647	>4	1	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	20/18/13	19/16/11	18/15/12
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
A = ! = N = (ANI)	I/OLI/-	ACTM DOOM		0.50	0.77	0.01

Acid Number (AN)

mg KOH/g ASTM D8045

0.77

0.52

0.91



OIL ANALYSIS REPORT

