

OIL ANALYSIS REPORT

JAL NM Machine Id MRC-202

Component

Compressor Fluid

LO-ASH ENGINE OIL SAE 40 (--- GAL)

Sample Rating Trend Junio222 Augio23 Sepi023 Nevi023



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Moor

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jun 202	12 Aug2023	Sep2023 N	ov2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60001646	TO60001452	TO60001175
Sample Date		Client Info		02 Nov 2023	06 Sep 2023	15 Aug 2023
Machine Age	hrs	Client Info		20877	19547	19527
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	2	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>25	2	2	1
Lead	ppm	ASTM D5185m	>25	4	2	2
Copper	ppm	ASTM D5185m	>50	25	22	23
Tin	ppm	ASTM D5185m	>15	3	3	3
Vanadium	ppm	ASTM D5185m		<1	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	37	40	40	41
Barium	ppm	ASTM D5185m	12	0	0	0
Molybdenum	ppm	ASTM D5185m	200	4	3	4
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m	5	12	16	10
Calcium	ppm	ASTM D5185m	1600	1303	1286	1340
Phosphorus	ppm	ASTM D5185m	300	332	297	304
Zinc	ppm	ASTM D5185m	400	390	348	349
Sulfur	ppm	ASTM D5185m	2600	2281	2487	2421
CONTAMINANTS	6	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	2	1
Sodium	ppm	ASTM D5185m		2	3	2
Potassium	ppm	ASTM D5185m	>20	<1	<1	0
Water	%	ASTM D6304	>0.1	0.014	0.025	0.011
ppm Water	ppm	ASTM D6304	>1000	147.4	250.6	118.0
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	535	394	1705
Particles >6µm		ASTM D7647	>2500	159	97	577
Particles >14µm		ASTM D7647	>320	10	10	49
Particles >21µm		ASTM D7647	>80	2	2	11
Particles >38µm		ASTM D7647	>20	0	1	0
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	16/14/10	16/14/10	18/16/13
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
A !	1/01::	10711 006 :-			0.40	

Acid Number (AN)

mg KOH/g ASTM D8045

0.10

0.12

0.555



OIL ANALYSIS REPORT

