

OIL ANALYSIS REPORT

Sample Rating Trend



Area 5509 CHAMPIONS DR Machine Id MRC-292 Component

Compressor Fluid TULCO LUBSOIL LPG WS 150 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	IATION	method	limit/base	3 Aug2023 Sep2023 Oct2023	history1	history2
Sample Number		Client Info		TO60001755	TO60001669	TO60001440
Sample Date		Client Info		05 Nov 2023	12 Oct 2023	05 Sep 2023
Machine Age	hrs	Client Info		6777	6541	6179
Oil Age	hrs	Client Info		0	0	0
Oil Changed	1110	Client Info		N/A	0 N/A	0 N/A
Sample Status				NORMAL	ABNORMAL	ATTENTION
				NOTIMAL	-	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m		0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	<1	<1	0
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>50	1	0	<1
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	99	107	126
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	<1	0	<1
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m	0	8	13	10
Calcium	ppm	ASTM D5185m	0	1277	1344	1236
Phosphorus	ppm	ASTM D5185m	0	306	305	255
Zinc	ppm	ASTM D5185m	0	322	332	272
Sulfur	ppm	ASTM D5185m	0	1662	1376	1036
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	12	2
Sodium	ppm	ASTM D5185m		2	2	3
Potassium	ppm	ASTM D5185m	>20	1	2	0
Water	%	ASTM D6304	>2.26	0.016	0.012	0.032
ppm Water	ppm	ASTM D6304	>22600	165.9	121.3	320.9
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	4214	▲ 12277	5176
Particles >6µm		ASTM D7647	>1300	1209	<u> </u>	1625
Particles >14µm		ASTM D7647	>320	64	86	84
Particles >21µm		ASTM D7647	>80	11	10	14
Particles >38µm		ASTM D7647	>20	2	0	0
Particles >71µm		ASTM D7647	>4	2	0	0
Oil Cleanliness		ISO 4406 (c)	>20/17/15	19/17/13	▲ 21/19/14	▲ 20/18/14
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.62	0.82	0.99





OIL ANALYSIS REPORT

Color

Bottom








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>2.26	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	151	131	132	130
Visc @ 100°C	cSt	ASTM D445	28	13.4	13.4	13.2
Viscosity Index (VI)	Scale	ASTM D2270	224	96	95	94
SAMPLE IMAGES		method	limit/base	current	history1	history2





Contact/Location: HERMAN GARZA - EOGMID