


## **OIL ANALYSIS REPORT**

### Sample Rating Trend







# MRC-322

Component

Compressor

NOT GIVEN (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		May2023	Jul2023 Aug2023	Sep2023 Oct2023	Nov2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60001751	TO60001672	TO60001435
Sample Date		Client Info		05 Nov 2023	12 Oct 2023	05 Sep 2023
Machine Age	hrs	Client Info		5267	4575	3065
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	1
Chromium	ppm	ASTM D5185m	>10	0	0	<1
Nickel	ppm	ASTM D5185m		0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>25	<1	<1	0
Lead	ppm	ASTM D5185m	>25	<1	0	0
Copper	ppm	ASTM D5185m	>50	1	<1	2
Tin	ppm	ASTM D5185m	>15	0	<1	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		103	98	113
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	<1
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m		7	11	9
Calcium	ppm	ASTM D5185m		1286	1349	1234
Phosphorus	ppm	ASTM D5185m		307	313	258
Zinc	ppm	ASTM D5185m		330	342	275
Sulfur	ppm	ASTM D5185m		2183	1562	1223
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	2	2
Sodium	ppm	ASTM D5185m		2	1	3
Potassium	ppm	ASTM D5185m	>20	<1	2	0
Water	%	ASTM D6304	>0.1	0.024	0.014	0.031
ppm Water	ppm	ASTM D6304	>1000	241.6	141.8	319.0
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	5192	3340	8309
Particles >6µm		ASTM D7647	>2500	1402	964	1705
Particles >14μm		ASTM D7647	>320	69	35	51
Particles >21µm		ASTM D7647	>80	12	6	9
Particles >38μm		ASTM D7647	>20	1	0	1
Particles >71μm		ASTM D7647	>4	1	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	20/18/13	19/17/12	20/18/13
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
A -! -! N! (ANI)		A OTA A DOG 45		0.50	0.05	0.45

Acid Number (AN)

mg KOH/g ASTM D8045

0.85

0.52

0.15



## **OIL ANALYSIS REPORT**

