

OIL ANALYSIS REPORT

OKLAHOMA 6794

Component

Diesel Engine

MYSTIK JT-8 SYN SUPER HD 15W40 (--- GAL)

Sample Rating Trend



Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

95/2022 May2022 Aug2022 Nov2022 Feb2023 May2023 Aug2023 Nov202							
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		WCMFA66693	WC0810721	WC0810728	
Sample Date		Client Info		08 Nov 2023	05 Oct 2023	11 Sep 2023	
Machine Age	hrs	Client Info		4962	4799	4677	
Oil Age	hrs	Client Info		2825	2662	2540	
Oil Changed		Client Info		Not Changd	Not Changd No	Not Changd	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINATION	٧	method	limit/base	current	history1	history2	
Fuel		WC Method	>5	<1.0	<1.0	<1.0 NEG	
Glycol		WC Method		NEG	NEG		
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>100	42	42	41	
Chromium	ppm	ASTM D5185m	>20	2	2	2	
Nickel	ppm	ASTM D5185m	>4	0	<1	0	
Titanium	ppm	ASTM D5185m		0	0	<1	
Silver	ppm	ASTM D5185m	>3	<1	<1	0	
Aluminum	ppm	ASTM D5185m	>20	7	8	8	
Lead	ppm	ASTM D5185m	>40	18	19	14	
Copper	ppm	ASTM D5185m	>330	54	54	57	
Tin	ppm	ASTM D5185m	>15	1	2	1	
Vanadium	ppm	ASTM D5185m		0	0	<1	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m		3	3	2	
Barium	ppm	ASTM D5185m		0	0	0	
Molybdenum	ppm	ASTM D5185m		13	13	13	
Manganese	ppm	ASTM D5185m		<1	1	<1	
Magnesium	ppm	ASTM D5185m		776	803	846	
Calcium	ppm	ASTM D5185m		1132	1183	1380	
Phosphorus	ppm	ASTM D5185m		903	989	1022	
Zinc	ppm	ASTM D5185m		1203	1260	1338	
Sulfur				2267	2435	3137	
CONTAMINANTS		method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	11	12	11	
Sodium	ppm	ASTM D5185m		15	16	17	
Potassium	ppm	ASTM D5185m	>20	15	18	19	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	1.3	1.2	1.2	
Nitration	Abs/cm	*ASTM D7624	>20	12.3	11.9	11.5	
Sulfation	Abs/.1mm	*ASTM D7415	>30	26.7	26.1	25.5	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414	>25	23.3	22.7	21.7	




OIL ANALYSIS REPORT




VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


18 - Abno	ormal	uan newen					
17-							
16 Base	\sim					*********	
314							_
13 - Abno	ormal						
12							-
11	- 2	2	7		22		-
Feb8/2	May6/2	Aug7/2	Nov8/2	-eb4/2	May6/2	Aug5/2	


FLUID PROPERTIES		method				history2	
	Visc @ 100°C	cSt	ASTM D445	15.6	14.6	14.6	14.7




GRAPHS













Laboratory Sample No.

Lab Number

: WCMFA66693 : 06008858 Unique Number : 10742620

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Diagnosed

: 15 Nov 2023 : 16 Nov 2023 Diagnostician : Sean Felton

Test Package : FLEET (Additional Tests: KV40) To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

LIBERTY DISPOSAL 6401 S EASTERN AVE OKLAHOMA CITY, OK

US 73149 Contact: Loran Cottle l.cottle@ldi89.com T: (910)970-0291 F: x:

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)