




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
DODGE 07 Dodge

Component
Diesel Engine

Fluid
MOBIL DELVAC 1300 SUPER15W40 (3 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0533301	WC0533300	WC0533299
Sample Date	Client Info		12 Nov 2023	19 Feb 2022	26 Dec 2020
Machine Age	mls	Client Info	245485	240270	235310
Oil Age	mls	Client Info	5000	4900	5000
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >130	16	24	25
Chromium	ppm	ASTM D5185m >10	<1	1	1
Nickel	ppm	ASTM D5185m >4	<1	0	<1
Titanium	ppm	ASTM D5185m >2	0	0	0
Silver	ppm	ASTM D5185m >2	<1	<1	<1
Aluminum	ppm	ASTM D5185m >20	3	3	3
Lead	ppm	ASTM D5185m >20	0	1	2
Copper	ppm	ASTM D5185m >125	<1	2	2
Tin	ppm	ASTM D5185m >4	<1	<1	<1
Antimony	ppm	ASTM D5185m	---	0	<1
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	69	52	44
Barium	ppm	ASTM D5185m 0	0	0	0
Molybdenum	ppm	ASTM D5185m 0	46	43	40
Manganese	ppm	ASTM D5185m	<1	<1	<1
Magnesium	ppm	ASTM D5185m 0	525	529	501
Calcium	ppm	ASTM D5185m	1654	1884	1756
Phosphorus	ppm	ASTM D5185m	745	810	743
Zinc	ppm	ASTM D5185m	905	1022	917
Sulfur	ppm	ASTM D5185m	2402	2240	2280

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	7	8	3
Sodium	ppm	ASTM D5185m	6	3	4
Potassium	ppm	ASTM D5185m >20	0	2	<1

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >6	1.3	1.5	1.7
Nitration	Abs/cm	*ASTM D7624 >20	8.7	10.1	10.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	24.4	27.0	26.5

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	20.8	23.7	23.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.4	8.79	10.1	8.55











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445 14	17.3	16.3	16.9

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0533301 **Received** : 16 Nov 2023
Lab Number : 06010297 **Diagnosed** : 20 Nov 2023
Unique Number : 10749441 **Diagnostician** : Sean Felton
Test Package : MOB 2

BEN CALDWELL
 17124 BECK CT
 SILOAM SPRINGS, AR
 US 72761
 Contact: BEN CALDWELL
 bencaldwell1@gmail.com
 T:
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)