


OIL ANALYSIS REPORT

[] WC-9259-0104-5 Chiller #4

Component Chiller

YORK TYPE K (--- GAL)





Recommendation

Resample at the next service interval to monitor. Insufficient sample was received to confirm all the routine laboratory tests.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| | | | Jun 2023 | Nov2023 | | |
|-------------------|---------|--------------|------------|-------------|-------------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0836493 | WC0784798 | |
| Sample Date | | Client Info | | 13 Nov 2023 | 19 Jun 2023 | |
| Machine Age | hrs | Client Info | | 13959 | 13090 | |
| Oil Age | hrs | Client Info | | 0 | 0 | |
| Oil Changed | | Client Info | | N/A | N/A | |
| Sample Status | | | | NORMAL | NORMAL | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >8 | 0 | <1 | |
| Chromium | ppm | ASTM D5185m | >2 | 0 | 0 | |
| Nickel | ppm | ASTM D5185m | | 0 | 0 | |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | |
| Aluminum | ppm | ASTM D5185m | >3 | 0 | 0 | |
| Lead | ppm | ASTM D5185m | >2 | 0 | 0 | |
| Copper | ppm | ASTM D5185m | >8 | 0 | <1 | |
| Tin | ppm | ASTM D5185m | >4 | <1 | 0 | |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Barium | ppm | ASTM D5185m | 0 | 0 | <1 | |
| Molybdenum | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Manganese | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Magnesium | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Calcium | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Phosphorus | ppm | ASTM D5185m | 5 | 1 | 0 | |
| Zinc | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Sulfur | ppm | ASTM D5185m | 10 | 8 | 0 | |
| CONTAMINANTS | ; | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >15 | 3 | 4 | |
| Sodium | ppm | ASTM D5185m | | 0 | 0 | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | 0 | |
| Water | % | ASTM D6304 | >0.01 | 0.047 | 0.058 | |
| ppm Water | ppm | ASTM D6304 | >100 | 474.2 | 588.0 | |
| FLUID CLEANLIN | IESS | method | limit/base | current | history1 | history2 |
| Particles >4μm | | ASTM D7647 | >10000 | 750 | 1340 | |
| Particles >6μm | | ASTM D7647 | >2500 | 152 | 548 | |
| Particles >14μm | | ASTM D7647 | >320 | 5 | 33 | |
| Particles >21µm | | ASTM D7647 | >80 | 2 | 4 | |
| Particles >38μm | | ASTM D7647 | >20 | 0 | 0 | |
| Particles >71µm | | ASTM D7647 | >4 | 0 | 0 | |
| Oil Cleanliness | | ISO 4406 (c) | >20/18/15 | 17/14/10 | 18/16/12 | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| A aid Number (AN) | I/OII/- | ACTM DODAE | 0.00 | 0.015 | 0.045 | |

Acid Number (AN)

mg KOH/g ASTM D8045 0.03

0.045

0.015



OIL ANALYSIS REPORT







Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** Test Package

: 06010955

: WC0836493 : 10750099 : PLANT

Received : 17 Nov 2023 Diagnosed : 04 Dec 2023

Diagnostician : Doug Bogart

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

10840 Guilford Road, Suites 406-407 Annapolis Junction, MD

US 20701 Contact: Susan Nord

susan.nord@chugachgov.com

T: (301)688-6363 F: (443)479-5666