

OIL ANALYSIS REPORT

Area LSS-9300-5 Machine Id SULLAIR 003-71174 - AMERICA TRUETSCHLER Component

Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.






NORMAL


| SAMPLE INFORM | NATION | method | limit/base | current | history1 | history2 |
|------------------|---------------|-------------|------------|-------------|----------|----------|
| Sample Number | | Client Info | | UCH06011013 | | |
| Sample Date | | Client Info | | 09 Nov 2023 | | |
| Machine Age | hrs | Client Info | | 23056 | | |
| Oil Age | hrs | Client Info | | 987 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATIO | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | | |
| Chromium | ppm | ASTM D5185m | >10 | 0 | | |
| Nickel | ppm | ASTM D5185m | | 0 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >25 | 0 | | |
| Lead | ppm | ASTM D5185m | >25 | 0 | | |
| Copper | ppm | ASTM D5185m | >50 | 0 | | |
| Tin | ppm | ASTM D5185m | >15 | <1 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | | 0 | | |
| Calcium | ppm | ASTM D5185m | | 0 | | |
| Phosphorus | ppm | ASTM D5185m | | 176 | | |
| Zinc | ppm | ASTM D5185m | | 0 | | |
| Sulfur | ppm | ASTM D5185m | | 504 | | |
| CONTAMINANTS | ; | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | <1 | | |
| Sodium | ppm | ASTM D5185m | | 0 | | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.25 | | |



OIL ANALYSIS REPORT

VISUAL





| | Wh | nite Metal | scalar | *Visual | NONE | NONE | | |
|------------|-------------------|----------------------------|-------------------------|-----------|--|-------------|--------------------|------------|
| | Yel | llow Metal | scalar | *Visual | NONE | NONE | | |
| | | ecipitate | scalar | *Visual | NONE | NONE | | |
| | Silt | - | scalar | *Visual | NONE | NONE | | |
| | | | | | | | | |
| | | bris | scalar | *Visual | NONE | NONE | | |
| | | nd/Dirt | scalar | *Visual | NONE | NONE | | |
| | App App | pearance | scalar | *Visual | NORML | NORML | | |
| | [≥] Od | or | scalar | *Visual | NORML | NORML | | |
| | Em | ulsified Water | scalar | *Visual | >0.1 | NEG | | |
| | Fre | e Water | scalar | *Visual | | NEG | | |
| | | | | | | | | |
| | | LUID PROPE | RHES | method | limit/base | current | history1 | history2 |
| | Vis | c @ 40°C | cSt | ASTM D445 | | 45.6 | | |
| | S | AMPLE IMAG | ES | method | limit/base | current | history1 | history2 |
| | | | | | | | | |
| | Col | lor | | | | | no image | no image |
| | Bot | ttom | | | | | no image | no image |
| | 10 8 | on-ferrous Me | tals | | EZ/GvoN | | | |
| | udd 4 2 0 EZ/6^oN | | | | Nov9/23 | | | |
| | 55 T | íscosity @ 40° | С | | | Acid Number | | |
| | A | Abnormal | | | Acid Number (mg KOH/g) 10 Brid Number (mg KOH/g) 10 CH (g) | | | |
| | 30 | | | | Q 0.2 | 4 | | |
| | (J-04) 45- | | | | 트 0.1 형 0.1 | 0 | | |
| | 40 A | Abnormal | | | 10.1 | 2 | | |
| | T | | | | - pg 0.0 | 16 | | |
| | 35 4 | | | | | | | |
| | Nov9/23 | | | | Nov9/23 | Nov9/23 | | |
| Laboratory | | earCheck USA CH06011013 | - 501 Madis Received | | ry, NC 2751 Nov 2023 | 3 LEWIS | SYSTEM AND 3915 | SERVICES C |

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: