


PROBLEM SUMMARY

GP-112 Machine Id B40832 - REXROTH HYD UNIT

Hydraulic System

PETRO CANADA PURITY FG AW HYDRAULIC 46 (130 GAL)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

We recommend you service the filters on this component. Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS ABNORMAL Sample Status ABNORMAL ABNORMAL Particles >4µm ASTM D7647 >10000 27611 49857 ▲ 27152 Particles >6µm ASTM D7647 >1300 3223 ▲ 7083 ▲ 3212 Particles >14µm ASTM D7647 >160 198 198 72 Particles >21µm ASTM D7647 >40 **52** 30 12 **Oil Cleanliness** ISO 4406 (c) >20/17/14 🔺 22/19/15 🔺 23/20/15 🔺 22/19/13


Customer Id: HORAUS Sample No.: WC0855968 Lab Number: 06011475 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Don Baldridge +1 <u>don.b505@comcast.net</u>

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>



RECOMMENDED AC	CTIONS					
Action	Status	Date	Done By	Description		
Change Filter			?	We recommend you service the filters on this component.		

HISTORICAL DIAGNOSIS



01 Aug 2023 Diag: Don Baldridge

We recommend you service the filters on this component. Resample at the next service interval to monitor.All component wear rates are normal. There is a high amount of particulates present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



view report

05 May 2023 Diag: Wes Davis

We recommend you service the filters on this component. We recommend an early resample to monitor this condition.All component wear rates are normal. There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The system cleanliness is above the acceptable limit for the target ISO 4406 cleanliness code. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.




08 Feb 2023 Diag: Doug Bogart

We recommend you service the filters on this component. Resample at the next service interval to monitor.All component wear rates are normal. There is a high amount of particulates present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.









OIL ANALYSIS REPORT

Area GP-112 Machine Id B40832 - REXROTH HYD UNIT

Hydraulic System

PETRO CANADA PURITY FG AW HYDRAULIC 46 (130 GAL)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




Sample Date Client Info 08 Nov 2023 01 Aug 2023 05 May 2023 Machine Age hrs Client Info 0 0 0 Oil Age hrs Client Info 0 0 0 Oil Changed Client Info N/A N/A ABNORMAL ABNORMAL ABNORMAL CONTAMINATION method limitbase current history1 history2 Water WC Method >0.05 NEG NEG NEG WEAR METALS method limitbase current history1 history2 Iron ppm ASTM 05185m >40 11 14 12 Chromium ppm ASTM 05185m >40 0 0 0 Ikinekel ppm ASTM 05185m >40 0 0 0 Ikinekel ppm ASTM 05185m >4 0 0 11 1 1 Ikinekel ppm ASTM 05185m 0 0 0 </th <th>SAMPLE INFORM</th> <th>MATION</th> <th>method</th> <th>limit/base</th> <th>current</th> <th>history1</th> <th>history2</th>	SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Machine Age hrs Client Info 0 0 0 0 Oil Age hrs Client Info 0 0 0 0 Oil Age hrs Client Info 0 0 0 0 Sample Status Client Info N/A N/A N/A N/A N/A CONTAMINATION method limit/base current history1 history2 Water WC Method >0.05 NEG NEG NEG Water WC Method >0.05 NEG NEG NEG Iron ppm ASTM 05185m >40 11 14 12 Chromium ppm ASTM 05185m >40 0 0 0 Nickel ppm ASTM 05185m >0 0 0 0 Silver ppm ASTM 05185m >60 <1	Sample Number		Client Info		WC0855968	WC0814192	WC0799613
Oil Age hrs Client Info 0 0 0 Oil Changed Client Info N/A N/A N/A N/A Sample Status Client Info N/A ABNORMAL ABNORMAL ABNORMAL CONTAMINATION method Imit/base current history1 history2 Water WC Method >0.05 NEG NEG NEG Wear WC Method >0.05 NEG NEG NEG fon ppm ASTM 05185m >40 11 14 12 Chromium ppm ASTM 05185m >40 0 0 0 Silver ppm ASTM 05185m >20 0 0 0 Silver ppm ASTM 05185m >40 0 0 0 Silver ppm ASTM 05185m >10 0 0 0 Capper ppm ASTM 05185m >60 <1	Sample Date		Client Info		08 Nov 2023	01 Aug 2023	05 May 2023
Oil Changed Client Info N/A N/A N/A ABNORMAL ABNORMAL ABNORMAL CONTAMINATION method limit/base current history1 history2 Water WC Method >0.05 NEG NEG NEG WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185m >40 11 14 12 Chromium ppm ASTM D5185m >20 0 0 0 Nickel ppm ASTM D5185m >40 0 0 0 Aluminum ppm ASTM D5185m >40 0 0 0 Qandium ppm ASTM D5185m >40 0 0 0 0 Qandium ppm ASTM D5185m >40 0 0 0 0 Qandium ppm ASTM D5185m 0 0 0 0 0 Qandium ppm	Machine Age	hrs	Client Info		0	0	0
Sample Status ABNORMAL ABNORMAL ABNORMAL ABNORMAL ABNORMAL ABNORMAL CONTAMINATION method limit/base current history1 history2 Water WC Method >0.05 NEG NEG NEG WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185n >40 11 14 12 Chromium ppm ASTM D5185n >20 0 0 0 Silver ppm ASTM D5185n >20 0 0 0 Silver ppm ASTM D5185n >4 0 0 0 Copper ppm ASTM D5185n >4 0 0 1 1 Tin ppm ASTM D5185n >4 0 0 0 0 Cadmium ppm ASTM D5185n 0 0 0 0 0 Barium ppm ASTM D5185	Oil Age	hrs	Client Info		0	0	0
CONTAMINATION method limit/base current history1 history2 Water WC Method >0.05 NEG NEG NEG Wear WC Method >0.05 NEG NEG NEG Wear WC Method >0.05 NEG Netor history1 history2 Iron ppm ASTM D5185m >40 11 14 12 Chromium ppm ASTM D5185m >20 0 0 0 Silver ppm ASTM D5185m >20 0 0 0 Silver ppm ASTM D5185m >10 0 0 0 Cadmium ppm ASTM D5185m >4 0 0 0 Vanadium ppm ASTM D5185m 0 0 0 0 Cadmium ppm ASTM D5185m 0 0 0 0 ASTM D5185m 0 0 0 0 0 0 <tr< td=""><td>Oil Changed</td><td></td><td>Client Info</td><td></td><th>N/A</th><td>N/A</td><td>N/A</td></tr<>	Oil Changed		Client Info		N/A	N/A	N/A
Water WC Method >0.015 NEG NEG NEG WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185m >40 11 14 12 Chromium ppm ASTM D5185m >4 <1 0 <1 Nickel ppm ASTM D5185m >4 <0 0 0 Silver ppm ASTM D5185m >40 0 0 0 Lead ppm ASTM D5185m >40 0 0 <1 Vanadium ppm ASTM D5185m >60 <1 1 1 Tin ppm ASTM D5185m >60 <1 0 <1 Vanadium ppm ASTM D5185m 0 0 0 0 Cadmium ppm ASTM D5185m 0 0 0 0 Baron ppm ASTM D5185m 0 0 0 0	Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS method limil/base current history1 history2 Iron ppm ASTM D5185m >40 11 14 12 Chromium ppm ASTM D5185m >40 11 14 12 Nickel ppm ASTM D5185m >20 0 0 0 Silver ppm ASTM D5185m >20 0 0 0 Aluminum ppm ASTM D5185m >40 0 0 0 Lead ppm ASTM D5185m >40 0 0 <11 1 Tin ppm ASTM D5185m >40 0 0 <11 0 Vanadium ppm ASTM D5185m >40 0 0 0 0 Vanadium ppm ASTM D5185m 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	CONTAMINATIO	N	method	limit/base	current	history1	history2
Iron ppm ASTM D5185m >40 11 14 12 Chromium ppm ASTM D5185m >20 0 0 0 Nickel ppm ASTM D5185m >20 0 0 0 Silver ppm ASTM D5185m 0 0 0 0 Aduminum ppm ASTM D5185m >10 0 0 0 Lead ppm ASTM D5185m >60 <1 1 1 Copper ppm ASTM D5185m >60 <1 1 1 Cadmium ppm ASTM D5185m 0 0 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 0 0 0 0 Maganese ppm ASTM D5185m 0 0 0 0 Magnesium ppm ASTM D5185m 0 <1 <1 1<	Water		WC Method	>0.05	NEG	NEG	NEG
Ppm ASTM D5185m >4 <1 0 <1 Nickel ppm ASTM D5185m >20 0 0 0 Silver ppm ASTM D5185m 0 0 0 0 Silver ppm ASTM D5185m 0 0 0 0 Auminum ppm ASTM D5185m >4 0 0 0 0 Lead ppm ASTM D5185m >60 <1	WEAR METALS		method	limit/base	current	history1	history2
Nickel ppm ASTM D5185m >20 0 0 0 Titanium ppm ASTM D5185m 0 0 0 0 Silver ppm ASTM D5185m 0 0 0 0 Aluminum ppm ASTM D5185m >4 0 0 0 0 Lead ppm ASTM D5185m >4 0 0 <1	Iron	ppm	ASTM D5185m	>40	11	14	12
Titanium ppm ASTM D5185m 0 0 0 0 Silver ppm ASTM D5185m 0 0 0 0 Aluminum ppm ASTM D5185m >44 0 0 0 0 Aluminum ppm ASTM D5185m >10 0 0 <1	Chromium	ppm	ASTM D5185m	>4	<1	0	<1
Silver ppm ASTM D5185m 0 0 0 Aluminum ppm ASTM D5185m >4 0 0 0 Lead ppm ASTM D5185m >10 0 0 <1	Nickel	ppm	ASTM D5185m	>20	0	0	0
Aluminum ppm ASTM D5185m >4 0 0 0 Lead ppm ASTM D5185m >10 0 0 <1	Titanium	ppm	ASTM D5185m		0	0	0
Lead ppm ASTM D5185m >10 0 0 <1 Copper ppm ASTM D5185m >60 <1	Silver	ppm	ASTM D5185m		0	0	0
Copper ppm ASTM D5185m >60 <1 1 1 Tin ppm ASTM D5185m >4 0 0 <1	Aluminum	ppm	ASTM D5185m	>4	0	0	0
Tin ppm ASTM D5185m >4 0 0 <1 Vanadium ppm ASTM D5185m 0 0 0 0 Cadmium ppm ASTM D5185m 0 0 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 0 0 0 2 Molybdenum ppm ASTM D5185m 0 0 0 0 Magnesium ppm ASTM D5185m 0 0 0 0 Calcium ppm ASTM D5185m 0 <1	Lead	ppm	ASTM D5185m	>10	0	0	<1
Vanadium ppm ASTM D5185m 0 <1 0 Cadmium ppm ASTM D5185m 0 0 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 0 0 0 0 Barium ppm ASTM D5185m 0 0 0 2 Molybdenum ppm ASTM D5185m 0 0 0 0 Manganese ppm ASTM D5185m 0 0 0 0 Calcium ppm ASTM D5185m 0 0 0 0 Calcium ppm ASTM D5185m 0 0 0 0 Sulfur ppm ASTM D5185m 5 0 4 29 21 Solicon ppm ASTM D5185m >20 3 3 4 Sodium ppm ASTM D5185m >20 0 <11	Copper	ppm	ASTM D5185m	>60	<1	1	1
Cadmium ppm ASTM D5185m 0 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 0 0 0 0 Barium ppm ASTM D5185m 0 0 0 2 Molybdenum ppm ASTM D5185m 0 0 0 0 Manganese ppm ASTM D5185m 0 0 0 0 Magnesium ppm ASTM D5185m 0 0 0 0 0 Calcium ppm ASTM D5185m 0 0 0 0 0 Magnesium ppm ASTM D5185m 0 422 497 429 20 Zinc ppm ASTM D5185m 5 0 4 29 261 Solitorn ppm ASTM D5185m 20 3 3 4 Sodium ppm ASTM D5185m 2	Tin	ppm	ASTM D5185m	>4	0	0	<1
ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 0 0 0 2 Molybdenum ppm ASTM D5185m 0 0 0 2 Molybdenum ppm ASTM D5185m 0 0 0 0 Marganese ppm ASTM D5185m 0 <1	Vanadium	ppm	ASTM D5185m		0	<1	0
Boron ppm ASTM D5185m 0 0 0 Barium ppm ASTM D5185m 0 0 2 Molybdenum ppm ASTM D5185m 0 0 0 Manganese ppm ASTM D5185m 0 0 0 Magnesium ppm ASTM D5185m 0 <1	Cadmium	ppm	ASTM D5185m		0	0	0
Barium ppm ASTM D5185m 0 0 2 Molybdenum ppm ASTM D5185m 0 0 0 Manganese ppm ASTM D5185m 0 0 0 Magnesium ppm ASTM D5185m 0 <1 <1 Calcium ppm ASTM D5185m 0 0 0 Phosphorus ppm ASTM D5185m 422 497 429 Zinc ppm ASTM D5185m 5 0 4 Sulfur ppm ASTM D5185m 581 1029 561 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 3 3 4 Potassium ppm ASTM D5185m >20 0 <1 1 Paticles >4µm ASTM D7647 >10000 27611 49857 27152 Paticles >6µm ASTM D7647 >1000 3223	ADDITIVES		method	limit/base	current	history1	history2
Molybdenum ppm ASTM D5185m 0 0 0 Manganese ppm ASTM D5185m 0 0 0 Magnesium ppm ASTM D5185m 0 <1	Boron	ppm	ASTM D5185m		0	0	0
Maganese ppm ASTM D5185m 0 0 0 Magnesium ppm ASTM D5185m 0 <1	Barium	ppm	ASTM D5185m		0	0	2
Magnesium ppm ASTM D5185m 0 <1 <1 Calcium ppm ASTM D5185m 0 0 0 Phosphorus ppm ASTM D5185m 422 497 429 Zinc ppm ASTM D5185m 422 497 429 Sulfur ppm ASTM D5185m 5 0 4 Sulfur ppm ASTM D5185m 5 0 4 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 3 3 4 Potassium ppm ASTM D5185m >20 3 3 4 FLUID CLEANLINESS method limit/base current history1 history2 Particles >4µm ASTM D7647 >10000 27611 49857 27152 Particles >6µm ASTM D7647 >10000 27611 49857 27152 Particles >1µm ASTM D7647	Molybdenum	ppm	ASTM D5185m		0	0	0
Calcium ppm ASTM D5185m 0 0 0 Phosphorus ppm ASTM D5185m 422 497 429 Zinc ppm ASTM D5185m 422 497 429 Zinc ppm ASTM D5185m 5 0 4 Sulfur ppm ASTM D5185m 381 1029 561 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 3 3 4 Sodium ppm ASTM D5185m >20 3 3 4 Potassium ppm ASTM D5185m >20 0 <1	Manganese	ppm	ASTM D5185m		0	0	0
Phosphorus ppm ASTM D5185m 422 497 429 Zinc ppm ASTM D5185m 5 0 4 Sulfur ppm ASTM D5185m 381 1029 561 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 3 3 4 Sodium ppm ASTM D5185m >20 3 3 4 Potassium ppm ASTM D5185m >20 0 <1	Magnesium	ppm	ASTM D5185m		0	<1	<1
ZincppmASTM D5185m504SulfurppmASTM D5185m3811029561CONTAMINANTSmethodlimit/basecurrenthistory1history2SiliconppmASTM D5185m>20334SodiumppmASTM D5185m>20334PotassiumppmASTM D5185m>200<1	Calcium	ppm	ASTM D5185m		0	0	0
SulfurppmASTM D5185m3811029561CONTAMINANTSmethodlimit/basecurrenthistory1history2SiliconppmASTM D5185m>20334SodiumppmASTM D5185m>20334PotassiumppmASTM D5185m>200<1	Phosphorus	ppm	ASTM D5185m		422	497	429
CONTAMINANTSmethodlimit/basecurrenthistory1history2SiliconppmASTM D5185m>20334SodiumppmASTM D5185m<1	Zinc	ppm	ASTM D5185m		5	0	4
Silicon ppm ASTM D5185m >20 3 3 4 Sodium ppm ASTM D5185m <1	Sulfur	ppm	ASTM D5185m		381	1029	561
Sodium ppm ASTM D5185m <1	CONTAMINANTS	6	method	limit/base	current	history1	history2
Potassium ppm ASTM D5185m >20 0 <1 1 FLUID CLEANLINESS method limit/base current history1 history2 Particles >4µm ASTM D7647 >10000 27611 4 49857 27152 Particles >6µm ASTM D7647 >1300 3223 7083 3212 Particles >6µm ASTM D7647 >160 198 198 72 Particles >14µm ASTM D7647 >40 52 30 12 Particles >21µm ASTM D7647 >10 2 1 0 Particles >38µm ASTM D7647 >10 2 1 0 Particles >71µm ASTM D7647 >3 0 0 0 Oil Cleanliness ISO 4406 (c) >20/17/14 22/19/15 23/20/15 22/19/13 FLUID DEGRADATION method limit/base current history1 history2	Silicon	ppm	ASTM D5185m	>20	3	3	4
FLUID CLEANLINESS method limit/base current history1 history2 Particles >4µm ASTM D7647 >10000 27611 49857 27152 Particles >6µm ASTM D7647 >1300 3223 7083 3212 Particles >14µm ASTM D7647 >160 198 198 72 Particles >21µm ASTM D7647 >40 52 30 12 Particles >38µm ASTM D7647 >10 2 1 0 Particles >71µm ASTM D7647 >3 0 0 0 Oil Cleanliness ISO 4406 (c) >20/17/14 22/19/15 23/20/15 22/19/13	Sodium	ppm	ASTM D5185m		<1	1	0
Particles >4μm ASTM D7647 >10000 27611 49857 27152 Particles >6μm ASTM D7647 >1300 3223 7083 3212 Particles >14μm ASTM D7647 >160 198 198 72 Particles >21μm ASTM D7647 >40 52 30 12 Particles >38μm ASTM D7647 >10 2 1 0 Particles >38μm ASTM D7647 >3 0 0 0 Oli Cleanliness ISO 4406 (c) >20/17/14 22/19/15 23/20/15 22/19/13	Potassium	ppm	ASTM D5185m	>20	0	<1	1
Particles >6μm ASTM D7647 >1300 3223 7083 3212 Particles >14μm ASTM D7647 >160 198 198 72 Particles >21μm ASTM D7647 >40 52 30 12 Particles >38μm ASTM D7647 >10 2 1 0 Particles >38μm ASTM D7647 >3 0 0 0 Particles >71μm ASTM D7647 >3 0 0 0 Oil Cleanliness ISO 4406 (c) >20/17/14 22/19/15 23/20/15 22/19/13 FLUID DEGRADATION method limit/base current history1 history2	FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >14µm ASTM D7647 >160 ▲ 198 198 72 Particles >21µm ASTM D7647 >40 ▲ 52 30 12 Particles >38µm ASTM D7647 >10 2 1 0 Particles >38µm ASTM D7647 >3 0 0 0 Particles >71µm ASTM D7647 >3 0 0 0 Oil Cleanliness ISO 4406 (c) >20/17/14 22/19/15 ▲ 23/20/15 ▲ 22/19/13	Particles >4µm		ASTM D7647	>10000	A 27611	49857	▲ 27152
Particles >21μm ASTM D7647 >40 52 30 12 Particles >38μm ASTM D7647 >10 2 1 0 Particles >37μm ASTM D7647 >3 0 0 0 Particles >71μm ASTM D7647 >3 0 0 0 Oil Cleanliness ISO 4406 (c) >20/17/14 22/19/15 23/20/15 22/19/13 FLUID DEGRADATION method limit/base current history1 history2	Particles >6µm		ASTM D7647	>1300	<u> </u>	A 7083	▲ 3212
Particles >38μm ASTM D7647 >10 2 1 0 Particles >71μm ASTM D7647 >3 0 0 0 Oil Cleanliness ISO 4406 (c) >20/17/14 22/19/15 23/20/15 22/19/13 FLUID DEGRADATION method limit/base current history1 history2	Particles >14µm		ASTM D7647	>160	198	1 98	72
Particles >71μm ASTM D7647 >3 0 0 0 Oil Cleanliness ISO 4406 (c) >20/17/14 22/19/15 23/20/15 22/19/13 FLUID DEGRADATION method limit/base current history1 history2	Particles >21µm		ASTM D7647	>40	<u> </u>	30	12
Oil Cleanliness ISO 4406 (c) >20/17/14 22/19/15 23/20/15 22/19/13 FLUID DEGRADATION method limit/base current history1 history2	Particles >38µm		ASTM D7647	>10	2	1	0
FLUID DEGRADATION method limit/base current history1 history2	Particles >71µm		ASTM D7647	>3	0	0	0
	Oil Cleanliness		ISO 4406 (c)	>20/17/14	A 22/19/15	▲ 23/20/15	▲ 22/19/13
Acid Number (AN) mg KOH/g ASTM D8045 0.26 0.18 0.174 0.16	FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
	Acid Number (AN)	mg KOH/g	ASTM D8045	0.26	0.18	0.174	0.16


Contact/Location: RYAN LOWE - HORAUS



OIL ANALYSIS REPORT


Bottom








Acid Number 0.40 KOH/g) .B 0.10 0.00 ah8/20 ua7/21 av4/77 h8/73 ov11/1 Aug9/1 10w28





Sample No. Lab Number :06011475 : 21 Nov 2023 Diagnosed Unique Number : 10750619 Diagnostician : Don Baldridge Test Package : IND 2 Contact: RYAN LOWE Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. rslowe@hormel.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: (507)437-5674 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (507)437-9805

Contact/Location: RYAN LOWE - HORAUS

no image

Page 4 of 4

US 55912