

OIL ANALYSIS REPORT

Sample Rating Trend







Machine Id **145** Component Hydraulic System Fluid NOT GIVEN (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2			
Sample Number		Client Info		PTK0004826					
Sample Date		Client Info		09 Nov 2023					
Machine Age	mths	Client Info		0					
Oil Age	mths	Client Info		0					
Oil Changed		Client Info		N/A					
Sample Status				NORMAL					
CONTAMINATION	١	method	limit/base	current	history1	history2			
Water		WC Method	>0.1	NEG					
WEAR METALS		method	limit/base	current	history1	history2			
Iron	ppm	ASTM D5185m	>20	0					
Chromium	ppm	ASTM D5185m	>10	0					
Nickel	ppm	ASTM D5185m	>10	0					
Titanium	ppm	ASTM D5185m		<1					
Silver	ppm	ASTM D5185m		0					
Aluminum	ppm	ASTM D5185m	>10	0					
Lead	ppm	ASTM D5185m	>10	0					
		ASTM D5185m	>75	45					
Copper Tin	ppm	ASTM D5185m		45 <1					
	ppm		>10						
Vanadium	ppm	ASTM D5185m		<1					
Cadmium	ppm	ASTM D5185m		0					
ADDITIVES		method	limit/base	current	history1	history2			
Boron	ppm	ASTM D5185m		0					
Barium	ppm	ASTM D5185m		0					
Molybdenum	ppm	ASTM D5185m		0					
Manganese	ppm	ASTM D5185m		0					
Magnesium	ppm	ASTM D5185m		0					
Calcium	ppm	ASTM D5185m		30					
Phosphorus	ppm	ASTM D5185m		265					
Zinc	ppm	ASTM D5185m		352					
Sulfur	ppm	ASTM D5185m		1427					
CONTAMINANTS		method	limit/base	current	history1	history2			
Silicon	ppm	ASTM D5185m	>20	<1					
Sodium	ppm	ASTM D5185m		<1					
Potassium	ppm		>20	0					
FLUID CLEANLIN		method	limit/base	current	history1	history2			
Particles >4µm		ASTM D7647		4041					
•			. 2500						
Particles >6µm		ASTM D7647		1318					
Particles >14µm		ASTM D7647	>320	100					
Particles >21µm		ASTM D7647		20					
Particles >38µm		ASTM D7647	>20	1					
Particles >71µm		ASTM D7647		0					
Oil Cleanliness		ISO 4406 (c)	>18/15	18/14					
FLUID DEGRADA	TION	method	limit/base	current	history1	history2			
Acid Number (AN)	mg KOH/g	ASTM D8045		0.17					
. ,	- 5		Contact/Location: BUTCH BLISS - EXOKENWA						


Report Id: EXOKENWA [WUSCAR] 06012360 (Generated: 11/21/2023 10:34:24) Rev: 1


Contact/Location: BUTCH BLISS - EXOKENWA



OIL ANALYSIS REPORT







	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris		*Visual	NONE	NONE		
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Sand/Dirt		*Visual	NONE	NONE		
2.800 2.3	Appearance		*Visual	NORML	NORML		
2	0001		*Visual	NORML	NORML		
	Emulsified Water		*Visual	>0.1	NEG		
	Free Water		*Visual		NEG		
	FLUID PROPERT	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		46.4		
	SAMPLE IMAGES	S	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
	Ferrous Alloys			101 500	Particle Count		
	10 iron			491,520			T26
	= 6 - mickel			122,880	-		-24
				30,720			-22
	2				1		
	0 2 3			7,680 E			+2
	Nov9/23			Nov9/23 [per 1 m])	1		-18
	Non-ferrous Metal	s		·편 480	1		
	50 T			ofpa			-24 -18 -18 -19
	40 - copper lead			.ESC(6vol) 1.020 480 150 150 150 150 150 150 150 150 150 15	1		14
	E 30 20			= 30	-		-12
	-20			5	Bharran 1	/	-10
	0				<b>Berwe</b> mal	1	\
	Nov9/23			Nov9/23	•		
				ž (		14µ 21µ	38µ 71µ
	Viscosity @ 40°C			0.20	Acid Number		
	Abnormal			(B/HO)			
	() () () () () () () () () () () () () (			¥ U.15	I		
				(B) (B) (B) (B) (B) (B) (B) (B) (C) (C) (C) (C) (C) (C) (C) (C) (C) (C			
				Z 0.05			
	35 4			0.00			
	Nov9/23			Nov9/23	Nov9/23		
Laboratory	: WearCheck USA - 5 : PTK0004826	501 Madiso <b>Received</b>		ry, NC 27513 Nov 2023	B EX	OTIC METALS	FORMING C 02 S 226TH S

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)