



# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**ENDEAVOR (S/N 2WB11198)**

Component  
**Center Main Engine**  
Fluid  
**NOT GIVEN (9 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0847403</b>	---	---
Sample Date	Client Info			<b>21 Oct 2023</b>	---	---
Machine Age	hrs	Client Info		<b>9413</b>	---	---
Oil Age	hrs	Client Info		<b>384</b>	---	---
Oil Changed	Client Info			<b>Not Chngd</b>	---	---
Sample Status				<b>NORMAL</b>	---	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>4.0		<b>&lt;1.0</b>	---	---
Water	WC Method	>0.1		<b>NEG</b>	---	---
Glycol	WC Method			<b>NEG</b>	---	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>75	<b>7</b>	---	---
Chromium	ppm	ASTM D5185m	>8	<b>0</b>	---	---
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	---	---
Titanium	ppm	ASTM D5185m	>3	<b>3</b>	---	---
Silver	ppm	ASTM D5185m	>2	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m	>15	<b>1</b>	---	---
Lead	ppm	ASTM D5185m	>18	<b>1</b>	---	---
Copper	ppm	ASTM D5185m	>80	<b>2</b>	---	---
Tin	ppm	ASTM D5185m	>14	<b>&lt;1</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	---	---
Cadmium	ppm	ASTM D5185m		<b>0</b>	---	---



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<b>101</b>	---	---
Barium	ppm	ASTM D5185m		<b>0</b>	---	---
Molybdenum	ppm	ASTM D5185m		<b>59</b>	---	---
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	---	---
Magnesium	ppm	ASTM D5185m		<b>433</b>	---	---
Calcium	ppm	ASTM D5185m		<b>1872</b>	---	---
Phosphorus	ppm	ASTM D5185m		<b>1038</b>	---	---
Zinc	ppm	ASTM D5185m		<b>1302</b>	---	---
Sulfur	ppm	ASTM D5185m		<b>3718</b>	---	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<b>3</b>	---	---
Sodium	ppm	ASTM D5185m	>75	<b>1</b>	---	---
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	---	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		<b>1.15</b>	---	---







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.1	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	95.1	---	---

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0847403      **Received** : 20 Nov 2023  
**Lab Number** : 06012604      **Diagnosed** : 21 Nov 2023  
**Unique Number** : 10751748      **Diagnostician** : Wes Davis  
**Test Package** : MAR 2 ( Additional Tests: KV40 )

**CITY EXPERIENCES - SEAWARD EXPLORER**  
 2825 5TH AVENUE  
 SAN DIEGO, CA  
 US 92103  
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: