

OIL ANALYSIS REPORT

Sample Rating Trend





Grand Blanc CAT 5 GBLM05BE

Component
Biogas Engine

CHEVRON HDAX 6500 LFG GAS ENGINE OIL (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: 200hr Oil Sample)

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


| SAMPLE INFORM | NOITAN | method | limit/base | current | history1 | history2 |
|---|---|--|---|---|--|---|
| Sample Number | | Client Info | | WC0870126 | WC0824976 | WC0824981 |
| Sample Date | | Client Info | | 14 Nov 2023 | 26 Oct 2023 | 22 Oct 2023 |
| Machine Age | hrs | Client Info | | 56458 | 55965 | 85800 |
| Oil Age | hrs | Client Info | | 233 | 0 | 0 |
| Oil Changed | | Client Info | | Changed | N/A | N/A |
| Sample Status | | | | NORMAL | ABNORMAL | ABNORMA |
| CONTAMINATION | N | method | limit/base | current | history1 | history2 |
| Fuel | | WC Method | >4.0 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.1 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >15 | 2 | 5 | 7 |
| Chromium | ppm | ASTM D5185m | >4 | <1 | 0 | <1 |
| Nickel | ppm | ASTM D5185m | >2 | 0 | <1 | <1 |
| Titanium | ppm | ASTM D5185m | | 0 | <1 | 0 |
| Silver | ppm | ASTM D5185m | >5 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | | 2 | 2 | 2 |
| Lead | ppm | ASTM D5185m | >9 | 0 | 1 | 2 |
| Copper | | ASTM D5185m | | <1 | 1 | 2 |
| Tin | ppm | ASTM D5185m | >14 | 2 | 2 | 2 |
| Vanadium | ppm | | >4 | 0 | 0 | 0 |
| | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 3 | 5 |
| Barium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | | <1 | 4 | 4 |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | 0 |
| Magnesium | ppm | | | | | |
| Coloium | ppiii | ASTM D5185m | | 11 | 0 | 15 |
| Calcium | ppm | ASTM D5185m ASTM D5185m | | 11 1987 | 0 1914 | 15 1978 |
| Caicium Phosphorus | | | | | | |
| | ppm | ASTM D5185m | | 1987 | 1914 | 1978 |
| Phosphorus | ppm ppm | ASTM D5185m ASTM D5185m | | 1987 295 | 1914 253 | 1978 327 |
| Phosphorus Zinc | ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m | limit/base | 1987 295 372 | 1914 253 342 | 1978 327 396 4312 |
| Phosphorus Zinc Sulfur | ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method | limit/base | 1987 295 372 3208 | 1914 253 342 3016 | 1978 327 396 4312 |
| Phosphorus Zinc Sulfur CONTAMINANTS | ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method | | 1987 295 372 3208 current | 1914 253 342 3016 history1 | 1978 327 396 4312 history2 |
| Phosphorus Zinc Sulfur CONTAMINANTS Silicon | ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m | >181 | 1987 295 372 3208 current 98 | 1914 253 342 3016 history1 | 1978 327 396 4312 history2 |
| Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium | ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m | >181 | 1987 295 372 3208 current 98 <1 | 1914 253 342 3016 history1 154 | 1978 327 396 4312 history2 159 0 |
| Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium | ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m | >181 | 1987 295 372 3208 current 98 <1 | 1914 253 342 3016 history1 154 2 <1 | 1978 327 396 4312 history2 159 0 |
| Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED | ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | >181 | 1987 295 372 3208 current 98 <1 2 | 1914 253 342 3016 history1 154 2 <1 | 1978 327 396 4312 history2 159 0 3 |
| Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % | ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D5185m | >181 >20 limit/base | 1987 295 372 3208 current 98 <1 2 current | 1914 253 342 3016 history1 154 2 <1 history1 0.1 | 1978 327 396 4312 history2 159 0 3 history2 |
| Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration | ppm ppm ppm ppm ppm ppm ppm Abs/cm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D5185m | >181 >20 limit/base >20 | 1987 295 372 3208 current 98 <1 2 current 0.1 6.1 | 1914 253 342 3016 history1 154 2 <1 history1 0.1 6.2 | 1978 327 396 4312 history2 159 0 3 history2 0.1 6.1 26.8 |
| Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation | ppm ppm ppm ppm ppm ppm ppm Abs/cm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D5185m *ASTM D5185m *ASTM D7844 *ASTM D7624 *ASTM D7415 | >181 >20 limit/base >20 >30 | 1987 295 372 3208 current 98 <1 2 current 0.1 6.1 23.3 | 1914 253 342 3016 history1 154 2 <1 history1 0.1 6.2 27.1 | 1978 327 396 4312 history2 159 0 3 history2 0.1 6.1 26.8 |
| Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA | ppm ppm ppm ppm ppm ppm ppm ppm ppm Abs/.1mm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7624 *ASTM D7415 method | >181 >20 limit/base >20 >30 limit/base | 1987 295 372 3208 | 1914 253 342 3016 history1 154 2 <1 history1 0.1 6.2 27.1 history1 | 1978 327 396 4312 history2 159 0 3 history2 0.1 6.1 26.8 |



OIL ANALYSIS REPORT










| VISUAL | | method | limit/base | current | history1 | history2 |
|-------------------------|--------|---------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG | NEG |


| LLUID PHOPER | TILO | memod | | | riistory i | History2 |
|--------------|------|-----------|------|------|------------|----------|
| Visc @ 100°C | cSt | ASTM D445 | 14.7 | 13.9 | 14.4 | 14.4 |


| Sever | re | | | | | | |
|------------|--------------------|----------|---------|--------------|------------|---------|-----------|
| Abno | rmal | | | | | | |
| l le | | | | | | 1 | |
| | | Λ. | ^ | | Λ | 11 | |
| | | 1 1 / | | 7.5 | - | / | 111 |
| V | 1 | V | 1 | V | ~1 | 1 | ~ |
| V | ~ | V | 7 | V | <u>ر ا</u> | 22 | ~ |
| V 0ct13/27 | V − 2Z//290 | Jan20/23 | Mar6/23 | Apr26/23 - 4 | Jun12/23 | Aug2/23 | Sep 28/23 |





















Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** Test Package : MOB 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC0870126 : 06012621 : 10751765

Received Diagnosed Diagnostician : Sean Felton

: 20 Nov 2023 : 21 Nov 2023 **EDL NA Recips-Grand Blanc**

Grand Blanc Powerstation, 2361 West Grand Blanc Road Grand Blanc, MI US 48439

Contact: Tony Saint Marie

tony.saintmarie@edlenergy.com T:

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: