

OIL ANALYSIS REPORT

Grand Blanc CAT 3 GBLM03BE

CHEVRON HDAX 6500 LFG GAS ENGINE OIL (--- GAL)

SAMPLE INFORMATION method

Sample Rating Trend



K

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: 200hr Oil Sample)

Machine Id

Component Biogas Engine

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

					motory	motoryz
Sample Number		Client Info		WC0870124	WC0824972	WC0825030
Sample Date		Client Info		14 Nov 2023	22 Sep 2023	13 Sep 2023
Machine Age	hrs	Client Info		79591	79223	78997
Oil Age	hrs	Client Info		213	207	1000
Oil Changed		Client Info		Changed	Changed	Not Changd
Sample Status				NORMAL	ABNORMAL	NORMAL
						-
CONTAMINATION	N	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>15	0	2	4
Chromium	ppm	ASTM D5185m	>4	0	0	0
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>6	1	<u> </u>	<1
Lead	ppm	ASTM D5185m	>9	0	0	2
Copper	ppm	ASTM D5185m	>14	12	3	6
Tin	ppm	ASTM D5185m	>4	<1	<1	2
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	15	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	4	2
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m		9	24	9
Calcium	ppm	ASTM D5185m		1831	1824	2111
Phosphorus	ppm	ASTM D5185m		277	319	300
Zinc	ppm	ASTM D5185m		345	377	375
Sulfur	ppm	ASTM D5185m		3123	3393	4437
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>181	45	73	130
Sodium	ppm	ASTM D5185m		4	2	3
Potassium	ppm	ASTM D5185m	>20	2	0	2
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	5.8	5.7	6.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.0	21.1	26.3
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	11.5	12.8	17.5
Acid Number (AN)	mg KOH/g	ASTM D8045	1.2	1.01	1.41	2.08
Base Number (BN)	mg KOH/g	ASTM D2896	4.5	3.57	1 .03	2.50
:30:37) Rev: 1					Submitted By:	

Page 1 of 2





Abnorma 12 11 Aug5/22 -

Sep16/22

Nov16/22

OIL ANALYSIS REPORT





		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
						NONE
				-		NONE
				-		NONE
				-		NORML
				-		
						NORML
			>0.1	-		NEG
		*Visual		NEG		NEG
		method		current		history2
	cSt	ASTM D445	14.7	13.5	13.8	14.0
				L = = d (m m m)		
Iron (ppm)			15			
Severe			10	Severe		
	111111			Abnormal	nanodina	
			mqq			
			5		\sim	1.
	V	~~	1		\sim	Mar 1
	1/23	0/23 - 0/23 -			1/23 1/23	0/23
Aug Sep16 Nov16 Jan11	Mar	May1 Jul1(Aua29	5	Aug. Sep16 Nov16	Jan 1 Mari	Jul10/23 Aug29/23
						~
12 Severe		1000000000000	6	Tennococcertan		
10-			5		*****	
			4 E -	T		
H 4			A 2			
2	~	~ m	11			
ug5/2 p16/2 v16/2	/ar1/2	w10/2 110/2 129/2	5	ug5/2 p16/2 v16/2	n11/2 1ar1/2 y10/2:	Jul10/23 Aug29/23
	M	Ma Ju		07 2	Jai M May	Ju
Copper (ppm)			250	Silicon (ppm)		
Severe				The second s		
8		Λ				
툍 10 - · · · · · · · · · · · · · · · · · ·		$ \rangle$	Ed 100	$\Lambda \Lambda \Lambda$	MN	111
5- ~ ^		IV	M	/ / / /	V ·	VVI
	~			and the second second second		
6/22 + (/22 + /23 +	/23	1/23 - 1/23 -	0		/23 - /23 -)/23 -
Aug5 Sep16 Jov16, lan11,	Mar1	Jull0 Jull0	0	Aug5 Sep16 Jov16,	Jan 11 Mar 1 Iay 10	Jul10/23 Aug29/23
		2 · 4			, ≥	A
18 -		122220000000000000	6.0			
			B/HO)	Base		1
Base			±84.0	Λ.		NA
을 14 정 Abnormal	~	\sim		WhA	mm	147
12			2.0 2 1.0		VV	
10			0.0	· · · · · · · · · · · · · · · · · · ·		
Aug5/22 Sep16/22 Nov16/22 Jan11/23	Mar1/23	May10/23 Jul10/23 Aug29/23		Aug5/22 Sep16/22 Nov16/22	Jan 11/23 Mar1/23 May10/23	Jul10/23 Aug29/23
La 10 10 10	Ma	lay' Jull ug2	D	ld v1	n la	all all
	Silt Debris Sand/Dirt Appearance Odor Emulsified Water Free Water Fluid PROPERT Visc @ 100°C GRAPHS Iron (ppm)	Silt scalar Debris scalar Sand/Dirt scalar Appearance scalar Odor scalar Emulsified Water scalar Free Water scalar Free Water scalar Fue Water scalar Free Water scalar Iron (ppm)	Silt scalar *Visual Debris scalar *Visual Appearance scalar *Visual Odor scalar *Visual Emulsified Water scalar *Visual Free Water scalar *Visual Free Water scalar *Visual FLUID PROPERTIES method Visc @ 100°C cSt ASTM D445 GRAPHS Iron (ppm) Copper (ppm) Aluminum (ppm) Copper (p	Silt scalar Visual NONE Debris scalar Visual NONE Sand/Dirt scalar Visual NONE Appearance scalar Visual NORML Odor scalar Visual NORML Emulsified Water scalar Visual >0.1 Free Water scalar Visual Visual Visual Visual Visca Visual Visca Visual Visca Visual Visca Visual Visca Visca 14.7 GRAPHS Iron (ppm) Aluminum (ppm) Aluminum (ppm) Copper (ppm) Copper (ppm) Viscosity @ 100°C	Silt scalar 'Visual NONE NONE Debris scalar 'Visual NONE NONE Sand/Dirt scalar 'Visual NONE NONE Appearance scalar 'Visual NORML NORML Odor scalar 'Visual NORML NORML Emulsified Water scalar 'Visual NORML NORML Emulsified Water scalar 'Visual NORML NORML Free Water scalar 'Visual NORML NORML Visc @ 100°C cSt ASTM D445 14.7 13.5 GRAPHS Iron (ppm) Copper (Silt scalar Visual NONE NONE NONE NONE Debris scalar Visual NONE NONE NONE Appearance scalar Visual NORML NORML NORML NORML Odor scalar Visual NORML NORML NORML NORML Emulsified Water scalar Visual NORML NORML NORML Tree Water scalar Visual NORML NORML NORML Visc @ 100°C cSt ASTM D445 14.7 13.5 13.8 GRAPHS Tron (ppm) Aluminum (ppm) Copper (p