




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
CATERPILLAR RH BEYMER
 Component
Port Genset
 Fluid
KENDALL SUPER-D XA 15W40 (--- GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0843976	WC0843981	---
Sample Date	Client Info		15 Nov 2023	19 Sep 2023	---
Machine Age	hrs	Client Info	17663	16943	---
Oil Age	hrs	Client Info	250	500	---
Oil Changed	Client Info		Changed	Changed	---
Sample Status			NORMAL	NORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>4.0	<1.0	<1.0	---
Water	WC Method	>0.1	NEG	NEG	---
Glycol	WC Method		NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>50	7	8	---
Chromium	ppm	ASTM D5185m	>4	<1	0	---
Nickel	ppm	ASTM D5185m	>2	<1	0	---
Titanium	ppm	ASTM D5185m		51	27	---
Silver	ppm	ASTM D5185m	>5	0	0	---
Aluminum	ppm	ASTM D5185m	>12	2	<1	---
Lead	ppm	ASTM D5185m	>17	<1	1	---
Copper	ppm	ASTM D5185m	>70	5	14	---
Tin	ppm	ASTM D5185m	>15	0	<1	---
Vanadium	ppm	ASTM D5185m		<1	0	---
Cadmium	ppm	ASTM D5185m		<1	0	---

ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	50	97	41	---
Barium	ppm	ASTM D5185m		9	0	---
Molybdenum	ppm	ASTM D5185m		38	47	---
Manganese	ppm	ASTM D5185m		<1	<1	---
Magnesium	ppm	ASTM D5185m	270	255	178	---
Calcium	ppm	ASTM D5185m	1900	2096	2198	---
Phosphorus	ppm	ASTM D5185m	1000	1022	939	---
Zinc	ppm	ASTM D5185m	1260	1207	1257	---
Sulfur	ppm	ASTM D5185m	3400	4334	3599	---

CONTAMINANTS

	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	4	3	---
Sodium	ppm	ASTM D5185m		4	15	---
Potassium	ppm	ASTM D5185m	>20	4	2	---

INFRA-RED




	method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844		0.1	0.1	---
Nitration	Abs/cm	*ASTM D7624	>20	9.3	10.2	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.7	19.9	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.4	17.2	---
Base Number (BN)	mg KOH/g	ASTM D2896	9.5	8.1	7.1	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.1	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.3	13.5	13.4

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0843976 **Received** : 20 Nov 2023
Lab Number : **06013168** **Diagnosed** : 24 Nov 2023
Unique Number : 10752312 **Diagnostician** : Jonathan Hester
Test Package : FLEET (Additional Tests: KV40)

SUPERIOR MARINE
 201 KELLY LANE
 CHESAPEAKE, OH
 US 45619

Contact: DARRELL KEARNS
 darrellkearns@superiormarineinc.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: