

OIL ANALYSIS REPORT

DICK LAVY Machine Id

NOT GIVEN (--- GAL)

DICK LAVY 4965 Component Rear Differential

Sample Rating Trend ISO October 1997

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. Please note that this is a corrected copy for laboratory elemental data updates.

Wear

All component wear rates are normal.

Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				Oct2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0843138		
Sample Date		Client Info		04 Oct 2023		
Machine Age	mls	Client Info		479		
Oil Age	mls	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	21		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>100	<1		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		165		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		1		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		8		
Phosphorus	ppm	ASTM D5185m		1009		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		22971		
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	9		
Sodium	ppm	ASTM D5185m		4		
Potassium	ppm	ASTM D5185m	>20	<1		
Water	%	ASTM D6304	>.2	0.029		
ppm Water	ppm	ASTM D6304	>2000	291.0		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	▲ 80029		
Particles >6µm		ASTM D7647	>5000	<u>4</u> 9113		
Particles >14μm		ASTM D7647	>640	70		
Particles >21µm		ASTM D7647	>160	12		
Particles >38μm		ASTM D7647	>40	1		
Particles >71μm		ASTM D7647	>10	0		
Oil Cleanliness		ISO 4406 (c)	>21/19/16	24/20/13		
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		3.53		



OIL ANALYSIS REPORT





Certificate L2367

Sample No. Lab Number **Unique Number**

: WC0843138 : 06013268

Received : 10752412

Diagnosed : 30 Nov 2023 Diagnostician : Doug Bogart : MOB 2 (Additional Tests: KF, KV100, PrtCount, VI)

Test Package To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

500 WHITE PLAINS RD

TARRYTOWN, NY US 10591

Contact: GIANNA CREDAROLI gianna.credaroli@basf.com

T:

F: