




# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id

**1201**

Component

**Diesel Engine**

Fluid

**DIESEL ENGINE OIL SAE 15W40 (--- GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0860414</b>	WC0827112	WC0810333
Sample Date	Client Info			<b>09 Nov 2023</b>	02 Aug 2023	26 Apr 2023
Machine Age	mls	Client Info		<b>290616</b>	285149	279592
Oil Age	mls	Client Info		<b>6000</b>	0	0
Oil Changed	Client Info			<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2		<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>8</b>	10	10
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	0
Lead	ppm	ASTM D5185m	>40	<b>3</b>	2	2
Copper	ppm	ASTM D5185m	>330	<b>4</b>	4	8
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	<b>67</b>	6	12
Barium	ppm	ASTM D5185m	10	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	100	<b>67</b>	68	79
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	450	<b>240</b>	387	397
Calcium	ppm	ASTM D5185m	3000	<b>1650</b>	1850	1837
Phosphorus	ppm	ASTM D5185m	1150	<b>936</b>	977	1043
Zinc	ppm	ASTM D5185m	1350	<b>1102</b>	1260	1274
Sulfur	ppm	ASTM D5185m	4250	<b>2923</b>	3779	3843

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>7</b>	4	6
Sodium	ppm	ASTM D5185m	>158	<b>5</b>	8	4
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	<1	<1
Glycol	%	*ASTM D2982		<b>0.0</b>	NEG	NEG


INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.8</b>	0.8	0.6
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.7</b>	9.1	9.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>21.8</b>	20.6	21.8

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>18.0</b>	17.4	18.9
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	<b>6.6</b>	7.4	7.1




# OIL ANALYSIS REPORT


Glycol Contamination



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.4	12.6	12.8

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : WC0860414 Received : 21 Nov 2023  
 Lab Number : 06013794 Diagnosed : 29 Nov 2023  
 Unique Number : 10752938 Diagnostician : Wes Davis  
 Test Package : FLEET ( Additional Tests: Glycol )

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**TOWN OF CHAPEL HILL**  
 6900 MILLHOUSE RD  
 CHAPEL HILL, NC  
 US 27516

Contact: Lisa DePasqua  
 ldepasqua@townofchapelhill.org

T: (919)696-4941

F: