

OIL ANALYSIS REPORT

SMISMI 26 ER4 (S/N S0068LFMLFL0AA3) Component

Refrigeration Compressor

USPI 1009-68 SC (230 GAL)

Recommendation

Resample at the next service interval to monitor.

Wear


cv bn,./All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.






		Jct2015 Dec.	2016 NOV2017 Dec2010	Dec2019 Dec2020 Aug2021	Junzuza	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USP0003539	USP246719	USP236216
Sample Date		Client Info		08 Nov 2023	20 Jun 2023	28 Apr 2022
Machine Age	hrs	Client Info		115814	112572	104731
Oil Age	hrs	Client Info		3242	642	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ATTENTION	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	0	2	20
Chromium	ppm	ASTM D5185m		0	0	<1
Nickel	ppm	ASTM D5185m	~~	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver		ASTM D5185m	>2	0	0	0
	ppm			0		
Aluminum	ppm	ASTM D5185m		-	<1	<1 0
Lead	ppm	ASTM D5185m	>2	0	<1	
Copper	ppm	ASTM D5185m		0	<1	<1
Tin	ppm	ASTM D5185m	>4	0	0	0
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	<1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	<1
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		1	0	11
Phosphorus	ppm	ASTM D5185m		0	0	12
Zinc	ppm	ASTM D5185m		0	0	2
Sulfur	ppm	ASTM D5185m	50	0	0	145
CONTAMINANTS	\$	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	0	<1	<1
Sodium	ppm	ASTM D5185m		0	0	2
Potassium	ppm	ASTM D5185m	>20	0	<1	0
Water	%	ASTM D6304	>0.01	0.008	0.008	0.007
ppm Water	ppm	ASTM D6304	>100	85	89.2	70.9
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	3873	1 9064	1 7724
Particles >6µm		ASTM D7647	>2500	571	1901	1776
Particles >14µm		ASTM D7647	>320	15	18	38
Particles >21µm		ASTM D7647	>80	3	5	5
Particles >38µm		ASTM D7647	>20	0	0	0
Particles >71µm		ASTM D7647		0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	- 19/16/11	▲ 21/18/11	▲ 21/18/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974	0.005	0.01	0.014	0.013
	ing NOLI/9	AU INI U374	0.000	0.01		


Report Id: SMISMINP [WUSCAR] 06015168 (Generated: 11/26/2023 13:37:30) Rev: 1


Contact/Location: ? ? - SMISMINP



OIL ANALYSIS REPORT







Ê 80

Selo 60

÷ 40

20

0

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.01	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	67	65.8	65.4	75.5
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
Color						

Bottom

