

# **OIL ANALYSIS REPORT**

## Area DPO [7328] **KAESER 1143 - NATIONAL METAL WARES** Component

Compressor

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




| SAMPLE INFORM    | NATION   | method      | limit/base | current     | history1    | history2 |
|------------------|----------|-------------|------------|-------------|-------------|----------|
| Sample Number    |          | Client Info |            | UCH06015206 | UCH05435525 |          |
| Sample Date      |          | Client Info |            | 15 Nov 2023 | 14 Dec 2021 |          |
| Machine Age      | hrs      | Client Info |            | 97197       | 88380       |          |
| Oil Age          | hrs      | Client Info |            | 8817        | 5444        |          |
| Oil Changed      |          | Client Info |            | Changed     | Changed     |          |
| Sample Status    |          |             |            | NORMAL      | NORMAL      |          |
| CONTAMINATION    | N        | method      | limit/base | current     | history1    | history2 |
| Water            |          | WC Method   | >0.05      | NEG         | NEG         |          |
| WEAR METALS      |          | method      | limit/base | current     | history1    | history2 |
| Iron             | ppm      | ASTM D5185m | >50        | 12          | 4           |          |
| Chromium         | ppm      | ASTM D5185m | >10        | 0           | 0           |          |
| Nickel           | ppm      | ASTM D5185m | >3         | 0           | 0           |          |
| Titanium         | ppm      | ASTM D5185m | >3         | 0           | 0           |          |
| Silver           | ppm      | ASTM D5185m | >2         | 0           | 0           |          |
| Aluminum         | ppm      | ASTM D5185m | >10        | 7           | 2           |          |
| Lead             | ppm      | ASTM D5185m | >10        | 0           | 0           |          |
| Copper           | ppm      | ASTM D5185m | >50        | <1          | 3           |          |
| Tin              | ppm      | ASTM D5185m | >10        | <1          | <1          |          |
| Antimony         | ppm      | ASTM D5185m |            |             | 0           |          |
| Vanadium         | ppm      | ASTM D5185m |            | 0           | 0           |          |
| Cadmium          | ppm      | ASTM D5185m |            | 0           | 0           |          |
| ADDITIVES        |          | method      | limit/base | current     | history1    | history2 |
| Boron            | ppm      | ASTM D5185m |            | 0           | 1           |          |
| Barium           | ppm      | ASTM D5185m |            | 0           | 0           |          |
| Molybdenum       | ppm      | ASTM D5185m |            | 0           | <1          |          |
| Manganese        | ppm      | ASTM D5185m |            | <1          | 0           |          |
| Magnesium        | ppm      | ASTM D5185m |            | 0           | <1          |          |
| Calcium          | ppm      | ASTM D5185m |            | 2           | <1          |          |
| Phosphorus       | ppm      | ASTM D5185m |            | 284         | 284         |          |
| Zinc             | ppm      | ASTM D5185m |            | 24          | 36          |          |
| Sulfur           | ppm      | ASTM D5185m |            | 477         | 441         |          |
| CONTAMINANTS     | 5        | method      | limit/base | current     | history1    | history2 |
| Silicon          | ppm      | ASTM D5185m | >25        | 0           | <1          |          |
| Sodium           | ppm      | ASTM D5185m |            | 0           | <1          |          |
| Potassium        | ppm      | ASTM D5185m | >20        | <1          | 0           |          |
| FLUID DEGRADA    | TION     | method      | limit/base | current     | history1    | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045  |            | 0.62        | 0.430       |          |




# **OIL ANALYSIS REPORT**

VISUAL



| EZSIDOON  | White Metal<br>Yellow Metal<br>Precipitate<br>Silt<br>Debris<br>Sand/Dirt<br>Appearance<br>Odor<br>Emulsified Water<br>Free Water | scalar *1<br>scalar *1<br>scalar *1<br>scalar *1<br>scalar *1<br>scalar *1<br>scalar *1<br>scalar *1<br>scalar *1 | Visual<br>Visual<br>Visual<br>Visual<br>Visual<br>Visual  | NONE<br>NONE<br>NONE<br>NONE<br>NONE<br>NORML<br>NORML<br>>0.05   | NONE<br>NONE<br>NONE<br>NONE<br>NORML<br>NORML<br>NEG<br>NEG | MODER<br>NONE<br>NONE<br>NONE<br>NORML<br>NORML<br>NORML<br>NEG<br>NEG<br>history1 | <br><br><br><br><br><br>history2     |
|---|---|---|---|---|--|--|--------------------------------------|
|   | Visc @ 40°C   | cSt A   | STM D445  |   | 45.2   | 45.4   |                                      |
|   | SAMPLE IMAGES   | S   | method  | limit/base  | current  | history1   | history2                             |
| Nov15/23  | Color   |   |   |   |  |  | no image                             |
|   | Bottom  |   |   |   |  |  | no image                             |
|   | GRAPHS<br>Ferrous Alloys  |   |   | Nov15/23  |  |  |                                      |
| (Lind)? A   | Viscosity @ 40°C  |   |   | (0.80<br>(0)HOX 0.60<br>(0)HOX 0.60 | Acid Number  |  | Nev15/23                             |
| Laboratory<br>Sample No.<br>Lab Number<br>Unique Number<br>Test Package<br>To discuss this sample report, co<br>* - Denotes test methods that an<br>Statements of conformity to speci | : 06015206<br>: 10754350<br>: IND 2<br>contact Customer Serv<br>re outside of the ISO 1   | Received<br>Diagnosed<br>Diagnostici<br>ice at 1-800<br>7025 scope  | : 22 N<br>: 26 N<br>an : Don<br>-237-1369.<br>of accredit | ov 2023<br>ov 2023<br>Baldridge<br>tation.  |  | DOWNERS  | SS STREET<br>S GROVE, IL<br>US 60515 |



Contact/Location: MICHAEL FERRIS - UCDELDOW