

OIL ANALYSIS REPORT

Sample Rating Trend



A-322

Component Rear Right Final Drive

JOHN DEERE HY-GARD HYD/TRANS (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition

The condition of the oil is acceptable for the time in service.


L)				Nov2023		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
ample Number		Client Info		WC0828489		
ample Date		Client Info		20 Nov 2023		
lachine Age	hrs	Client Info		6566		
il Age	hrs	Client Info		566		
il Changed		Client Info		Not Changd		
ample Status				NORMAL		
CONTAMINATION	J	method	limit/base	current	history1	history2
V ater		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
on	ppm	ASTM D5185m	>500	52		
hromium	ppm	ASTM D5185m	>10	<1		
lickel	ppm	ASTM D5185m	>10	0		
itanium	ppm	ASTM D5185m		<1		
ilver	ppm	ASTM D5185m		0		
luminum	ppm	ASTM D5185m	>25	1		
ead	ppm	ASTM D5185m	>25	<1		
opper	ppm	ASTM D5185m	>50	5		
in	ppm	ASTM D5185m	>10	0		
anadium	ppm	ASTM D5185m	210	0		
admium		ASTM D5185m		0		
	ppm		limit/book			
ADDITIVES		method	limit/base	current	history1	history2
oron	ppm	ASTM D5185m	6	6		
arium	ppm		0	0		
lolybdenum	ppm	ASTM D5185m	0	<1		
langanese	ppm	ASTM D5185m		<1		
lagnesium	ppm	ASTM D5185m	145	107		
alcium	ppm	ASTM D5185m	3570	3567		
hosphorus	ppm	ASTM D5185m	1290	1021		
inc	ppm	ASTM D5185m	1640	1278		
ulfur	ppm	ASTM D5185m		4067		
CONTAMINANTS		method	limit/base	current	history1	history2
ilicon	ppm	ASTM D5185m	>75	4		
odium	ppm	ASTM D5185m		0		
otassium	ppm	ASTM D5185m	>20	3		
VISUAL		method	limit/base	current	history1	history2
/hite Metal	scalar	*Visual	NONE	NONE		
	scalar	*Visual	NONE	NONE		
ellow Metal	Scalai	Viodai	_			
	scalar	*Visual	NONE	NONE		
recipitate						
recipitate ilt	scalar	*Visual	NONE	NONE		
recipitate ilt ebris	scalar scalar	*Visual *Visual	NONE NONE	NONE NONE		
recipitate ilt ebris and/Dirt	scalar scalar scalar	*Visual *Visual *Visual	NONE NONE	NONE NONE NONE		
recipitate ilt ebris and/Dirt ppearance	scalar scalar scalar scalar	*Visual *Visual *Visual *Visual	NONE NONE NONE	NONE NONE NONE		
ellow Metal recipitate ilt lebris and/Dirt ppearance dor mulsified Water	scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual	NONE NONE NONE NORML	NONE NONE NONE NONE NORML		





OIL ANALYSIS REPORT



FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	57.0	50.4		
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image









Certificate L2367

Laboratory Sample No. Lab Number Test Package : CONST

: WC0828489 : 06015516 Unique Number : 10754660

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 22 Nov 2023 Diagnosed

: 27 Nov 2023 Diagnostician : Jonathan Hester

DUKE LAZZARA 4201 FAYETTEVILLE RD RALEIGH, NC US 27603

Contact: NICK DIXON NICK.DIXON@DUKELAZZAM.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (919)760-7797 F:

Report Id: DUKRAL [WUSCAR] 06015516 (Generated: 11/27/2023 18:48:28) Rev: 1

Contact/Location: NICK DIXON - DUKRAL