Sullivan Palatek.

OIL ANALYSIS REPORT

PALLUBE 32 SULLIVAN PALATEK 1806080002 - WEST MEMPHIS STEEL Component

Compressor

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCS06016586	UCS05942338	
Sample Date		Client Info		15 Nov 2023	28 Aug 2023	
Machine Age	hrs	Client Info		24483	23241	
Oil Age	hrs	Client Info		1200	0	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m		<1	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>25	<1	0	
Lead	ppm	ASTM D5185m	>25	<1	0	
Copper	ppm	ASTM D5185m	>50	<1	<1	
Tin	ppm	ASTM D5185m	>15	2	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1	0	0	
Barium	ppm	ASTM D5185m	730	402	480	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m	0.0	0	<1	
Magnesium	ppm	ASTM D5185m	0	1	<1	
Calcium	ppm	ASTM D5185m	0	2	2	
Phosphorus	ppm	ASTM D5185m	0	4	8	
Zinc	ppm	ASTM D5185m	0	0	0	
Sulfur	ppm	ASTM D5185m	590	569	775	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	
Sodium	ppm	ASTM D5185m		83	23	
Potassium	ppm	ASTM D5185m	>20	5	2	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.14	0.092	0.20	



OIL ANALYSIS REPORT

VISUAL



1	Precipitate Silt	scalar scalar	*Visual *Visual	NONE NONE	NONE NONE	NONE NONE	
	Debris	scalar	*Visual	NONE	NONE	NONE	
-	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
5/23	Appearance	scalar	*Visual	NORML	NORML	NORML	
Nov	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPERT	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	42.8	43.0	41.3	
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Nov15/23 +	Color						no image
	Bottom						no image
	GRAPHS						
	Ferrous Alloys						
1							
	anneae chromium						
bpm	4						
	2						
	8/23			5/23 -			
	Aug2			Nov1			
	Non-ferrous Meta	s					
1	°T						
	o - seeseeseeseeseeseeseeseeseeseeseeseesee						
bpm	6						
	2						
	.8/23			5/23			
	Aug2			Nov1			
	Viscosity @ 40°C				Acid Number		
5	Abnormal			0.25			
- 4	-			HOX 0.20			
(40°C	Base			Ë 0.19	Base		
₹3 ₄	0 Abnormal			² 0.10	+		
	-			2 0.05			
3							
	Aug28			Nov15,	Aug28,		
:	WearCheck USA - 5	501 Madis	son Ave., Ca	ry, NC 27513	3	BLAKE AND	PENDLETC
		Received	d : 24 l	Nov 2023			-
:	06016586	Diagnos		Nov 2023			MEMPHIS, T
er :	06016586	Diagnos Diagnost		athan Hester			MEMPHIS, 1 US 381: JAY GIANNI
	1 mqg 1 mgg	Appearance Odor Emulsified Water Free Water FLUID PROPERT Visc @ 40°C SAMPLE IMAGES Color Bottom GRAPHS Ferrous Alloys	Appearance scalar Odor scalar Emulsified Water scalar Free Water scalar Free Water scalar FLUID PROPERTIES Visc @ 40°C cSt SAMPLE IMAGES Color Bottom GRAPHS Ferrous Alloys 10 6 4 2 0 0 0 0 0 0 0 0 0 0 0 0 0	Appearance scalar *Visual Odor scalar *Visual Emulsified Water scalar *Visual Free Water scalar *Visual Free Water scalar *Visual FLUID PROPERTIES method Visc @ 40°C cSt ASTM D445 SAMPLE IMAGES method Color Bottom GRAPHS Ferrous Alloys function intervention of the state of the s	Appearance scalar *Visual NORML Odor scalar *Visual NORML Emulsified Water scalar *Visual >0.1 Free Water scalar *Visual >0.1 Free Water scalar *Visual >0.1 Free Water scalar *Visual FLUID PROPERTIES method limit/base Visc @ 40°C cSt ASTM D445 42.8 SAMPLE IMAGES method limit/base Color Bottom GRAPHS Ferrous Alloys 000 000 000 000 000 000 000 000 000	Appearance scalar *Visual NORML NORML Odor scalar *Visual NORML NORML Emulsified Water scalar *Visual >0.1 NEG Free Water scalar *Visual >0.1 NEG Free Water scalar *Visual NORML NORML Visc @ 40°C cSt ASTM D445 42.8 43.0 SAMPLE IMAGES method imit/base current Color GRAPHS Ferrous Alloys USC @ 40°C cost astm cost ast	Appearance scalar *Visual NORML NORML NORML NORML Odor scalar *Visual NORML NORML NORML NORML Emulsified Water scalar *Visual >0.1 NEG NEG Free Water scalar *Visual >0.1 NEG NEG Free Water scalar *Visual >0.1 NEG NEG FLUID PROPERTIES method limit/base current history1 Visc @ 40°C cSt ASTM D445 42.8 43.0 41.3 SAMPLE IMAGES method limit/base current history1 Color GRAPHS Ferrous Alloys 1 0 0 0 0 0 0 0 0 0 0 0 0 0