


OIL ANALYSIS REPORT

ROTO Z [1396480]Machine Id ATLAS COPCO 100CA-CMP-100B - NRG SEWARD (S/N AIF118345)

Component

Compressor





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Aug2016 Nov2017 Aug2021 Aug2023 Nov2023					
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		UCH06016591	UCH05936222	UCH05326781	
Sample Date		Client Info		02 Nov 2023	10 Aug 2023	06 Aug 2021	
Machine Age	hrs	Client Info		125907	0	0	
Oil Age	hrs	Client Info		0	0	0	
Oil Changed		Client Info		Not Changd	Changed	N/A	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2	
Water		WC Method		NEG	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>50	0	0	0	
Chromium	ppm	ASTM D5185m		0	0	0	
Nickel	ppm	ASTM D5185m	70	<1	<1	0	
Titanium	ppm	ASTM D5185m		0	0	0	
Silver	ppm	ASTM D5185m		0	0	<1	
Aluminum	ppm	ASTM D5185m	\15	0	0	0	
Lead	ppm	ASTM D5185m	>65	0	0	0	
Copper	ppm	ASTM D5185m	>65	0	0	0	
Tin	ppm	ASTM D5185m	>10	<1	0	0	
Antimony	ppm	ASTM D5185m	>10			0	
Vanadium	ppm	ASTM D5185m		0	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES	ррііі	method	limit/base	current	history1	history2	
Boron	10 10 100	ASTM D5185m	IIIIIIIIIIII		0	0	
	ppm			0	1		
Barium	ppm	ASTM D5185m		0		0	
Molybdenum	ppm	ASTM D5185m		0	0	0	
Manganese	ppm	ASTM D5185m		0	0	0	
Magnesium	ppm	ASTM D5185m		<1		2	
Calcium	ppm	ASTM D5185m		<1 269	<1 213	213	
Phosphorus	ppm	ASTM D5185m		0	0	0	
Zinc Sulfur	ppm	ASTM D5185m		1202	1301	354	
	ppm	ASTM D5185m		-			
CONTAMINANTS		method	limit/base		history1	history2	
Silicon	ppm	ASTM D5185m	>35	2	0	0	
Sodium	ppm	ASTM D5185m		<1	0	0	
Potassium	ppm	ASTM D5185m	>20	<1	<1	<1	
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2	
Acid Number (AN)	mg KOH/g	ASTM D8045		0.101	0.152	0.061	




OIL ANALYSIS REPORT




VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		63.8	63.3	64.1
SAMPLE IMAGES		method	limit/base	current	history1	history2

Ferrous Alloys

Non-ferrous Metals









Laboratory Sample No. Lab Number **Unique Number**

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 06016591

: UCH06016591 : 10755735

Received Diagnosed

: 24 Nov 2023 : 28 Nov 2023 Diagnostician : Jonathan Hester **AIR TECHNOLOGIES INC (PIT)** 310 PLUM INDUSTRIAL CT

PITTSBURGH, PA US 15239

Contact: MIKE STRAZZERA

mike.strazzera@aircompressors.com

T: (724)327-2818 F: (412)788-4799

Test Package : IND 2 Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

Color

Bottom

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCAIRPIT [WUSCAR] 06016591 (Generated: 11/29/2023 19:40:19) Rev: 1