

# **OIL ANALYSIS REPORT**

Machine Id MTS-6

Component **Hydraulic System** 

**CONOCO MEGAFLOW AW 46 (--- GAL)** 

# Sample Rating Trend



## **DIAGNOSIS**

### Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is a high amount of particulates present in the oil.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

|                 |        | Jul2022      | ! Nov2022  | Apr2023 N    | ov2023            |             |
|-----------------|--------|--------------|------------|--------------|-------------------|-------------|
| SAMPLE INFORM   | MATION | method       | limit/base | current      | history1          | history2    |
| Sample Number   |        | Client Info  |            | WC0692517    | WC0739961         | WC0646242   |
| Sample Date     |        | Client Info  |            | 16 Nov 2023  | 30 Apr 2023       | 10 Nov 2022 |
| Machine Age     | hrs    | Client Info  |            | 2831         | 2753              | 0           |
| Oil Age         | hrs    | Client Info  |            | 0            | 0                 | 0           |
| Oil Changed     |        | Client Info  |            | Not Changd   | Not Changd        | N/A         |
| Sample Status   |        |              |            | ABNORMAL     | ABNORMAL          | NORMAL      |
| CONTAMINATION   | ١      | method       | limit/base | current      | history1          | history2    |
| Water           |        | WC Method    | >0.05      | NEG          | NEG               | NEG         |
| WEAR METALS     |        | method       | limit/base | current      | history1          | history2    |
| Iron            | ppm    | ASTM D5185m  | >20        | 1            | 3                 | 4           |
| Chromium        | ppm    | ASTM D5185m  | >10        | 0            | 0                 | <1          |
| Nickel          | ppm    | ASTM D5185m  | >10        | 0            | 0                 | 0           |
| Titanium        | ppm    | ASTM D5185m  |            | 0            | 0                 | 0           |
| Silver          | ppm    | ASTM D5185m  |            | 0            | <1                | 0           |
| Aluminum        | ppm    | ASTM D5185m  | >10        | 0            | 0                 | <1          |
| Lead            | ppm    | ASTM D5185m  | >20        | 0            | <1                | <1          |
| Copper          | ppm    | ASTM D5185m  | >20        | 5            | 6                 | 5           |
| Tin             | ppm    | ASTM D5185m  | >10        | 0            | 0                 | <1          |
| Vanadium        | ppm    | ASTM D5185m  |            | 0            | 0                 | 0           |
| Cadmium         | ppm    | ASTM D5185m  |            | <1           | <1                | <1          |
| ADDITIVES       |        | method       | limit/base | current      | history1          | history2    |
| Boron           | ppm    | ASTM D5185m  |            | 88           | 116               | 91          |
| Barium          | ppm    | ASTM D5185m  |            | 0            | 0                 | 0           |
| Molybdenum      | ppm    | ASTM D5185m  |            | 0            | 0                 | <1          |
| Manganese       | ppm    | ASTM D5185m  |            | <1           | <1                | <1          |
| Magnesium       | ppm    | ASTM D5185m  |            | 7            | 8                 | 9           |
| Calcium         | ppm    | ASTM D5185m  |            | 2613         | 3029              | 2848        |
| Phosphorus      | ppm    | ASTM D5185m  |            | 915          | 1048              | 918         |
| Zinc            | ppm    | ASTM D5185m  |            | 1132         | 1312              | 1160        |
| Sulfur          | ppm    | ASTM D5185m  |            | 4639         | 5658              | 5614        |
| CONTAMINANTS    |        | method       | limit/base | current      | history1          | history2    |
| Silicon         | ppm    | ASTM D5185m  | >15        | 10           | 11                | 10          |
| Sodium          | ppm    | ASTM D5185m  |            | 2            | 0                 | 2           |
| Potassium       | ppm    | ASTM D5185m  | >20        | 0            | 2                 | 0           |
| FLUID CLEANLIN  | ESS    | method       | limit/base | current      | history1          | history2    |
| Particles >4µm  |        | ASTM D7647   | >5000      | <b>12665</b> | <b>△</b> 16139    | 532         |
| Particles >6µm  |        | ASTM D7647   | >1300      | <b>3277</b>  | ▲ 5008            | 69          |
| Particles >14µm |        | ASTM D7647   | >160       | <u>252</u>   | <b>▲</b> 326      | 11          |
| Particles >21µm |        | ASTM D7647   | >40        | <u>^</u> 74  | <b>△</b> 63       | 3           |
| Particles >38µm |        | ASTM D7647   | >10        | 6            | 5                 | 0           |
| Particles >71µm |        | ASTM D7647   | >3         | 1            | 0                 | 0           |
| Oil Cleanliness |        | ISO 4406 (c) | >19/17/14  | <u> </u>     | <b>△</b> 21/20/16 | 16/13/11    |
| FLUID DEGRADA   | TION   | method       | limit/base | current      | history1          | history2    |
|                 |        |              |            |              |                   |             |

Acid Number (AN)

mg KOH/g ASTM D8045 0.38

0.85

0.71



# OIL ANALYSIS REPORT







Certificate L2367

Laboratory Sample No. Lab Number

: WC0692517

: 06026367 **Unique Number** : 10776158 Test Package : MOB 2 To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 06 Dec 2023 Received Diagnosed : 07 Dec 2023 : Jonathan Hester Diagnostician

**AES USA - EVERETT** 3003 W CASINO RD BLDG 40-26 DR S2 EVERETT, WA

US 98204-1910 Contact: TIM FELLER

tim.feller@aes-gse.com T: (425)266-4649

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)