

# **OIL ANALYSIS REPORT**

### Sample Rating Trend







# CATERPILLAR 374 10553 (S/N TNX10028)

Right Swing Drive
Fluid
NOT GIVEN (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil

## **Fluid Condition**


The condition of the oil is acceptable for the time in service.

		0et2022	Dec2022 Feb2023	Mar2023 Mar2023 Sep2023	Nov2023	
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0879392	WC0831308	WC0755209
Sample Date		Client Info		28 Nov 2023	19 Sep 2023	30 May 2023
Machine Age	hrs	Client Info		6338	5561	4858
Oil Age	hrs	Client Info		777	703	1173
Oil Changed	0	Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>400	13	19	38
Chromium	ppm	ASTM D5185m	>10	0	<1	0
Nickel	ppm		>10	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm		>25	0	0	0
Lead	ppm	ASTM D5185m	>50	0	0	0
Copper		ASTM D5185m	>200	<1	<1	<1
	ppm			0		
Tin	ppm	ASTM D5185m	>10		0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		167	168	100
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	<1	0
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m		0	4	2
Calcium	ppm	ASTM D5185m		66	271	1577
Phosphorus	ppm	ASTM D5185m		324	373	511
Zinc	ppm	ASTM D5185m		23	87	360
Sulfur	ppm	ASTM D5185m		1687	2033	2305
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	1	3	9
Sodium	ppm	ASTM D5185m		2	0	1
Potassium	ppm	ASTM D5185m	>20	0	<1	0
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
23:09) Ray: 1	Journal	riodai			ation: MIKE WV	


Contact/Location: MIKE WYATT - TRANEW





## **OIL ANALYSIS REPORT**



FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		101	103	115
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image
0.04.04.0						











Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10776591 Test Package : CONST

: WC0879392 : 06026800

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 06 Dec 2023 Diagnosed Diagnostician : Don Baldridge

: 08 Dec 2023

TRADER CONSTRUCTION CO. PO DRAWER 1578 NEW BERN, NC

US 28563 Contact: MIKE WYATT

F: (252)638-4871

mwyatt@traderconstruction.com T: (252)633-1399

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)