



PROBLEM SUMMARY



Machine Id 8341648 (S/N 1056) Component

Compressor Fluid KAESER SIGMA (OEM) S-460 (--- GAL)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

| PROBLEMATIC TEST RESULTS | | | | | | | | | | |
|--------------------------|--------------|---------|-------------------|----------|--|--|--|--|--|--|
| Sample Status | | | ATTENTION | NORMAL | | | | | | |
| Particles >14µm | ASTM D7647 | >80 | <u> </u> | 37 | | | | | | |
| Oil Cleanliness | ISO 4406 (c) | >/17/13 | 19/17/14 | 18/16/12 | | | | | | |

Customer Id: SDSINM Sample No.: KC122958 Lab Number: 06027750 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Doug Bogart +1 (800)237-1369 x4016 <u>dougb@wearcheckusa.com</u>

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS

20 Sep 2022 Diag: Don Baldridge



Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





OIL ANALYSIS REPORT

Sample Rating Trend

ISO

Machine Id 8341648 (S/N 1056) Component

Compressor Fluid KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 |
|------------------|---------------|--------------|------------|------------------|-------------|----------|
| Sample Number | | Client Info | | KC122958 | KC85948 | |
| Sample Date | | Client Info | | 28 Nov 2023 | 20 Sep 2022 | |
| Machine Age | hrs | Client Info | | 1905 | 815 | |
| Oil Age | hrs | Client Info | | 0 | 815 | |
| Oil Changed | | Client Info | | N/A | Changed | |
| Sample Status | | | | ATTENTION | NORMAL | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | | ASTM D5185m | >50 | <1 | <1 | |
| Chromium | ppm | ASTM D5185m | | <1 | 0 | |
| Nickel | ppm | | | 0 | | |
| | ppm | ASTM D5185m | >3 | | 0 | |
| Titanium | ppm | ASTM D5185m | | <1 | 0 | |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | |
| Aluminum | ppm | ASTM D5185m | | 2 | 0 | |
| Lead | ppm | ASTM D5185m | >10 | 0 | <1 | |
| Copper | ppm | ASTM D5185m | | 3 | 1 | |
| Tin | ppm | | >10 | 0 | 0 | |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | |
| Barium | ppm | ASTM D5185m | 90 | 5 | 9 | |
| Molybdenum | ppm | ASTM D5185m | | 0 | 0 | |
| Manganese | ppm | ASTM D5185m | | 0 | <1 | |
| Magnesium | ppm | ASTM D5185m | 90 | 59 | 71 | |
| Calcium | ppm | ASTM D5185m | 2 | 0 | 1 | |
| Phosphorus | ppm | ASTM D5185m | | 31 | 3 | |
| Zinc | ppm | ASTM D5185m | | 2 | 7 | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | <1 | <1 | |
| Sodium | ppm | ASTM D5185m | | 12 | 8 | |
| Potassium | ppm | ASTM D5185m | >20 | 34 | 11 | |
| Water | % | ASTM D6304 | >0.05 | 0.025 | 0.024 | |
| ppm Water | ppm | ASTM D6304 | >500 | 255 | 245.1 | |
| FLUID CLEANLIN | IESS | method | limit/base | current | history1 | history2 |
| Particles >4µm | | ASTM D7647 | | 3304 | 2239 | |
| Particles >6µm | | ASTM D7647 | >1300 | 829 | 640 | |
| Particles >14µm | | ASTM D7647 | >80 | <u> </u> | 37 | |
| Particles >21µm | | ASTM D7647 | >20 | 20 | 8 | |
| Particles >38µm | | ASTM D7647 | >4 | 0 | 1 | |
| Particles >71µm | | ASTM D7647 | >3 | 0 | 0 | |
| Oil Cleanliness | | ISO 4406 (c) | >/17/13 | 1 9/17/14 | 18/16/12 | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.30 | 0.36 | |
| | | | | | | |



OIL ANALYSIS REPORT

method

*Visual

*Visual

*Visua

*Visual

*Visual

*Visual

*Visual

*Visual

method

ASTM D445

method

scalar *Visual

scalar *Visual

scalar

scalar

scalar

scalar

scalar

scalar

scalar

scalar

cSt

limit/base

NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

limit/base

limit/base

491,52

122,880

30.720 7,680

480

120

31

(^{0.50} (⁰/HOX) 0.40

Ē 0.30

ੂੰ 0.20

Acid

Nov28/23

: 07 Dec 2023

: 08 Dec 2023

: Doug Bogart

0.10

0.00

lov/28/73

per 1 1,920

>0.05

46

current NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

curren

current

Particle Count

Acid Number

NEG

NEG

47.5

history1

NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

history

history1

NEG

NEG

43.9

history2

history

history2

no image

no image

4406

:1999 Cle

14

VISUAL

White Metal

Yellow Metal

Precipitate

Silt

Debris

Odor

Color

Sand/Dirt

Appearance

Free Water

Visc @ 40°C

GRAPHS

Ferrous Alloys


Non-ferrous Metals


Viscosity @ 40°C


Emulsified Water

FLUID PROPERTIES

SAMPLE IMAGES







Test Package : IND 2 Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

Abnorma

Sep20/22

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Received

Diagnosed

Diagnostician

Contact/Location: Service Manager - SDSINM

214

T:

F: