




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
4EK05286

Component
Biogas Engine

Fluid
MAHLER Q8 Mahler G8 SAE 40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| SAMPLE INFORMATION | | method | limit/base | current | history1 | history2 |
|--------------------|-------------|-------------|------------|--------------------|-------------|-------------|
| Sample Number | Client Info | | | WC0660937 | WC0660934 | WC0660935 |
| Sample Date | Client Info | | | 04 Dec 2023 | 31 Oct 2023 | 30 Oct 2023 |
| Machine Age | hrs | Client Info | | 81953 | 81828 | 81828 |
| Oil Age | hrs | Client Info | | 3 | 447 | 447 |
| Oil Changed | Client Info | | | N/A | N/A | N/A |
| Sample Status | | | | NORMAL | ABNORMAL | ABNORMAL |

| CONTAMINATION | | method | limit/base | current | history1 | history2 |
|---------------|-----------|--------|------------|----------------|----------|----------|
| Fuel | WC Method | >4.0 | | <1.0 | <1.0 | <1.0 |
| Water | WC Method | >0.1 | | NEG | NEG | NEG |
| Glycol | WC Method | | | NEG | NEG | NEG |

| WEAR METALS | | method | limit/base | current | history1 | history2 |
|-------------|-----|-------------|------------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m | >45 | 5 | 7 | 7 |
| Chromium | ppm | ASTM D5185m | >2 | 0 | <1 | <1 |
| Nickel | ppm | ASTM D5185m | >2 | 0 | <1 | <1 |
| Titanium | ppm | ASTM D5185m | | 0 | <1 | <1 |
| Silver | ppm | ASTM D5185m | >5 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >10 | 2 | 5 | 5 |
| Lead | ppm | ASTM D5185m | >5 | 0 | 2 | 2 |
| Copper | ppm | ASTM D5185m | >14 | 2 | 4 | 3 |
| Tin | ppm | ASTM D5185m | >13 | <1 | 3 | 3 |
| Vanadium | ppm | ASTM D5185m | | 0 | <1 | <1 |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | 0 |

| ADDITIVES | | method | limit/base | current | history1 | history2 |
|------------|-----|-------------|------------|--------------|----------|----------|
| Boron | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Barium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | | 0 | <1 | <1 |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | <1 |
| Magnesium | ppm | ASTM D5185m | | 7 | 8 | 7 |
| Calcium | ppm | ASTM D5185m | | 2161 | 2135 | 2083 |
| Phosphorus | ppm | ASTM D5185m | | 374 | 322 | 313 |
| Zinc | ppm | ASTM D5185m | | 440 | 418 | 413 |
| Sulfur | ppm | ASTM D5185m | | 2753 | 3809 | 3757 |




| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
|--------------|-----|-------------|------------|--------------|----------|----------|
| Silicon | ppm | ASTM D5185m | >200 | 56 | ▲ 211 | ▲ 204 |
| Sodium | ppm | ASTM D5185m | | 1 | 2 | 2 |
| Potassium | ppm | ASTM D5185m | >20 | <1 | 2 | 2 |

| INFRA-RED | | method | limit/base | current | history1 | history2 |
|-----------|----------|-------------|------------|-------------|----------|----------|
| Soot % | % | *ASTM D7844 | | 0 | 0 | 0 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 4.7 | 7.0 | 7.4 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 16.3 | 15.2 | 15.7 |

| FLUID DEGRADATION | | method | limit/base | current | history1 | history2 |
|-------------------|----------|-------------|------------|-------------|----------|----------|
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 9.2 | 10.6 | 11.4 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.97 | 1.17 | 1.18 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 8.0 | 9.33 | 4.66 | 4.67 |











OIL ANALYSIS REPORT



| VISUAL | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 | |
|------------------|--------|------------|---------|-------------|----------|------|
| Visc @ 100°C | cSt | ASTM D445 | 13.2 | 13.3 | 13.5 | 13.6 |

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0660937 **Received** : 07 Dec 2023
Lab Number : **06028777** **Diagnosed** : 11 Dec 2023
Unique Number : 10778568 **Diagnostician** : Don Baldrige
Test Package : MOB 2

BI-COUNTY
 3214 DOVER RD
 WOODLAWN, TN
 US 37191

Certificate L2367 **Contact: KEVIN WEAVER**
 To discuss this sample report, contact Customer Service at 1-800-237-1369. kevin.weaver@cubedistrictenergy.com
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T:
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: