

OIL ANALYSIS REPORT

Sample Rating Trend



JSF TCCEAU7195 Component

Hydraulic System ANDEROL ROYCO 500 (30 GAL)

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. Counts X100.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


				Dec2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0862391		
Sample Date		Client Info		06 Dec 2023		
Machine Age	mls	Client Info		0		
Dil Age	mls	Client Info		0		
Dil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	DN	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>20	0		
Chromium	ppm	ASTM D5185m	>20	0		
Nickel	ppm	ASTM D5185m	>20	0		
Fitanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	<1		
.ead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>20	0		
Fin	ppm	ASTM D5185m	>20	۰ <1		
/anadium	ppm	ASTM D5185m	>20	0		
Cadmium		ASTM D5185m		0		
	ppm			-		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
<i>I</i> agnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		1105		
linc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		0		
CONTAMINANT	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	1		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	3		
FLUID CLEANLI	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	5100		
Particles >6µm		ASTM D7647	>1300	2700		
Particles >14μm		ASTM D7647	>160	600		
Particles >21µm		ASTM D7647	>40	100		
· Particles >38μm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Dil Cleanliness		ISO 4406 (c)	>20/17/14	13/12/10		
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.06	0.19		
· /	- 0					




OIL ANALYSIS REPORT









NONE White Metal *Visual NONE scalar Yellow Metal *Visual NONE NONE scalar Precipitate scalar *Visua NONE NONE Silt scalar *Visual NONE NONE NONE Debris *Visual NONE scalar NONE NONE Sand/Dirt scalar *Visual NORML Appearance scalar *Visual NORML Odor *Visual NORML NORML scalar **Emulsified Water** scalar *Visual >0.05 NEG Free Water scalar *Visual NEG FLUID PROPERTIES Visc @ 40°C cSt ASTM D445 25.4 25.3 SAMPLE IMAGES Color no image no image Bottom no image no image GRAPHS Ferrous Alloys Particle Count 491,52 122,880 30 720 7,68 Dec6/23. Jec6/23 4406 per 1 1,920 :1999 Cle Non-ferrous Metals 480 120 14 31 14 21µ Viscosity @ 40°C Acid Number 30 @^{0.2} 28 HOX 0.15 () 26 b 0.10 zz 24 Abnorma Jaco 5 22 Acid 20 0.00 Dec6/23 -EATON AEROSPACE LLC Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : WC0862391 Received : 08 Dec 2023 15 DURANT AVE

: 12 Dec 2023

: Doug Bogart



Test Package : IND 2 Contact: RYAN KUNKEL Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. ryankunkel@eaton.com;ZachJolly@eaton.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Diagnosed

Diagnostician

Lab Number

Unique Number

: 06029977

: 10779768

F:

BETHEL, CT

T: (203)796-6041

US 06801