




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
LIEBHERR LTM 1060 3.1 AT7822 (S/N 57822)

Component
Diesel Engine

Fluid
DIESEL ENGINE OIL 10W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		HPL0003796	HPL0001559	HPL0001398
Sample Date	Client Info		06 Jan 2024	15 Nov 2022	13 Jul 2022
Machine Age	hrs	Client Info	11527	6329	70008
Oil Age	hrs	Client Info	0	0	0
Oil Changed	Client Info		N/A	N/A	N/A
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	8	8	11
Chromium	ppm	ASTM D5185m >5	0	<1	<1
Nickel	ppm	ASTM D5185m >5	0	1	0
Titanium	ppm	ASTM D5185m	0	0	0
Silver	ppm	ASTM D5185m >3	0	6	<1
Aluminum	ppm	ASTM D5185m >15	4	0	3
Lead	ppm	ASTM D5185m >30	<1	12	<1
Copper	ppm	ASTM D5185m >125	2	3	3
Tin	ppm	ASTM D5185m >5	0	3	<1
Vanadium	ppm	ASTM D5185m	0	<1	0
Cadmium	ppm	ASTM D5185m	0	<1	<1

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 250	5	56	31
Barium	ppm	ASTM D5185m 10	1	0	0
Molybdenum	ppm	ASTM D5185m 100	562	521	637
Manganese	ppm	ASTM D5185m	0	<1	<1
Magnesium	ppm	ASTM D5185m 450	1006	967	908
Calcium	ppm	ASTM D5185m 3000	2536	2524	2889
Phosphorus	ppm	ASTM D5185m 1150	1091	1041	1064
Zinc	ppm	ASTM D5185m 1350	1263	1113	1260
Sulfur	ppm	ASTM D5185m 4250	8370	13817	13032

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >60	8	11	10
Sodium	ppm	ASTM D5185m	3	0	1
Potassium	ppm	ASTM D5185m >20	0	3	2

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.3	0.3	0.4
Nitration	Abs/cm	*ASTM D7624 >20	12.1	9.6	10.9
Sulfation	Abs/.1mm	*ASTM D7415 >30	36.8	38.0	40.0

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	40.1	36.4	39.0
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	11.93	14.5	13.6











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	13.1	13.9	13.5

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : HPL0003796 **Recieved** : 08 Jan 2024
Lab Number : 06054154 **Diagnosed** : 09 Jan 2024
Unique Number : 10820103 **Diagnostician** : Sean Felton
Test Package : MOB 2

STEVENSON CRANE
 410 STEVENSON DR
 BOLINGBROOK, IL
 US 60440
 Contact: JOE HAMMOND
 joe@stevensoncrane.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: