

OIL ANALYSIS REPORT

Area **5C07 CHEVROLET SILVERADO TVK6819**

Transmission

{not provided} (--- GAL)

Sample Rating Trend



Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.


| | | | | Dec2023 | | |
|------------------|--------|-------------|------------|-------------|----------|-------------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | ARI0006828 | | |
| Sample Date | | Client Info | | 22 Dec 2023 | | |
| Machine Age | mls | Client Info | | 5243 | | |
| Oil Age | mls | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATIO | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >200 | 2 | | |
| Chromium | ppm | ASTM D5185m | >10 | <1 | | |
| Nickel | ppm | ASTM D5185m | | <1 | | |
| Titanium | ppm | ASTM D5185m | | <1 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >50 | 2 | | |
| Lead | ppm | ASTM D5185m | >50 | - <1 | | |
| Copper | ppm | ASTM D5185m | >200 | <1 | | |
| Tin | ppm | ASTM D5185m | >10 | <1 | | |
| Vanadium | ppm | ASTM D5185m | >10 | 0 | | |
| Cadmium | ppm | ASTM D5185m | | <1 | | |
| | ррпп | | | <u> </u> | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 198 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 86 | | |
| Manganese | ppm | ASTM D5185m | | <1 | | |
| Magnesium | ppm | ASTM D5185m | | 154 | | |
| Calcium | ppm | ASTM D5185m | | 1889 | | |
| Phosphorus | ppm | ASTM D5185m | | 1009 | | |
| Zinc | ppm | ASTM D5185m | | 1155 | | |
| Sulfur | ppm | ASTM D5185m | | 4341 | | |
| CONTAMINANTS | 3 | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >50 | 5 | | |
| Sodium | ppm | ASTM D5185m | | 1 | | |
| Potassium | ppm | ASTM D5185m | >20 | 1 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| 1 TOO TTUIO | Joalai | Vioudi | | 1124 | | I ADOCEODAL |





OIL ANALYSIS REPORT













Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10820365

: ARI0006828 : 06054416 Test Package : CONST

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved : 08 Jan 2024 Diagnosed : 09 Jan 2024

Diagnostician : Wes Davis

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

INSITUFORM TECHNOLOGIES, INC

709 EAST ORDNANCE ROAD SUITE 501

BALTIMORE, MD US 21226

Contact: ALBERT FRIEDRICH AFRIEDRICH@INSITUFORM.COM

T: (240)388-1832

F: