

OIL ANALYSIS REPORT

Area SFG-200 [262992] Machine Id AK10008947 - PENROSE BREWING CO

Compressor

{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





NORMAL


| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
|------------------|---------------|-------------|------------|-------------|----------|----------|
| Sample Number | | Client Info | | UFD06055425 | | |
| Sample Date | | Client Info | | 16 Oct 2023 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATION | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | | |
| Chromium | ppm | ASTM D5185m | >10 | 0 | | |
| Nickel | ppm | ASTM D5185m | | 0 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >25 | 0 | | |
| Lead | ppm | ASTM D5185m | >25 | 0 | | |
| Copper | ppm | ASTM D5185m | >50 | <1 | | |
| Tin | ppm | ASTM D5185m | >15 | 0 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | | 0 | | |
| Calcium | ppm | ASTM D5185m | | 3 | | |
| Phosphorus | ppm | ASTM D5185m | | 130 | | |
| Zinc | ppm | ASTM D5185m | | 28 | | |
| Sulfur | ppm | ASTM D5185m | | 0 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 0 | | |
| Sodium | ppm | ASTM D5185m | | 1 | | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | | |
| FLUID DEGRADA | | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.09 | | |



OIL ANALYSIS REPORT

Acid Number





| VISUAL | | methou | | | Thistory I | riistoi yz |
|-------------------------|-------------|--------------|--|------------|--------------------|------------------------------|
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| FLUID PROPER | TIES | method | limit/base | current | history1 | history2 |
| Visc @ 40°C | cSt | ASTM D445 | | 45.1 | | |
| SAMPLE IMAGE | | method | limit/base | current | history1 | history2 |
| | .0 | method | IIIII/base | | nistory | Thistory 2 |
| Color | | | | | no image | no image |
| Bottom | | | | | no image | no image |
| GRAPHS | | | | | | |
| Ferrous Alloys | | | | | | |
| 0 T | | | | | | |
| 8- iron | | | | | | |
| 6 - nickel | | | | | | |
| 4 | | | | | | |
| | | | | | | |
| 2 | | | | | | |
| 0 23 | | | 23 | | | |
| 0ct16/23 | | | 0ct16/23 | | | |
| Non-ferrous Meta | ls | | | | | |
| copper | | | | | | |
| 6 - tin | | | | | | |
| 4 - | | | | | | |
| 2 | | | | | | |
| 0L | | | ~ | | | |
| 0ct16/23 | | | 0ct16/23 | | | |
| ∽ Viscosity @ 40°C | | | 0 | Acid Numb | | |
| ⁵ T | | | _€ 0.10 | Acid Numbe | =1 | |
| 0 - Abnormal | | | (b)H00 0.08 (b)H00 0.08 (b)H00 0.04 (b)H00 0.04 (b)H00 0.02 (c)H00 0.02 (c)H00 0.02 (c)H00 0.02 (c)H00 0.02 (c)H00 0.03 (c)H00 | 3 | | |
| 5- | | | ٤ 0.06 | i | | |
| 0 - Abnormal | | | - ⁴ 0.04 | | | |
| T | | | ~ 0.02 | 2 | | |
| 54 | | | | | | 2 |
| 0ct16/23 | | | 0ct16/23 | 0ct16/23 | | 0ct16/23 |
| | | | | | | |
| WearCheck USA - | | | | 3 | | |
| UFD06055425 06055425 | Recievee | | Jan 2024 Jan 2024 | | | 0 ALBION AVE IAUMBURG, IL |
| 10821374 | Diagnos | | n Baldridge | | 50F | US 60193 |
| IND 2 | Diagnos | | Daidiidye | | Conta | ct: ED DIENEF |
| ntact Customer Serv | vice at 1-8 | 800-237-1369 | 9. | e | ed.diener@fluidair | |
| | 17005 000 | | litation | , | т. | (047)670 0000 |

To discuss this sample report, contact Customer Service at 1-800-237-1369.

C+ IAN°CI

Laboratory Sample No. Lab Number Unique Number Test Package

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

F:

T: (847)678-8388