

OIL ANALYSIS REPORT

SAMPLE INCODMATION

Sample Rating Trend VIS DEBRIS

Machine Id KAESER 7365952 Component

Compressor Fluid KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

Contamination

High concentration of visible dirt/debris present in the oil.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KC124833	KC124468	KC110678
Sample Date		Client Info		14 Nov 2023	16 Aug 2023	23 May 2023
Machine Age	hrs	Client Info		13791	12572	11558
Oil Age	hrs	Client Info		0	0	4333
Oil Changed		Client Info		N/A	N/A	Not Changd
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	<u>⊳50</u>	0	0	<1
Chromium	ppm	ASTM D5185m		0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m		0	<1	1
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m		3	6	3
Tin	ppm	ASTM D5185m	>10	۔ <1	0	0
Vanadium	ppm	ASTM D5185m	210	0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	27	0	18
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	90	70	22	46
Calcium	ppm	ASTM D5185m	2	1	0	0
Phosphorus	ppm	ASTM D5185m		4	0	4
Zinc	ppm	ASTM D5185m		0	0	0
CONTAMINANTS	6	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1	1	<1
Sodium	ppm	ASTM D5185m		15	7	10
Potassium	ppm	ASTM D5185m	>20	4	1	3
Water	%	ASTM D6304	>0.05	0.016	0.018	0.019
ppm Water	ppm	ASTM D6304	>500	169	180.7	198.9
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647			20425	6367
Particles >6µm		ASTM D7647	>1300		▲ 7516	2 645
Particles >14 μ m		ASTM D7647	>80		A 760	A 313
Particles >21µm		ASTM D7647	>20		1 77	A 77
Particles >38µm		ASTM D7647	>4		3	1
Particles >71µm		ASTM D7647	>3		1	0
Oil Cleanliness		ISO 4406 (c)	>/17/13		▲ 22/20/17	▲ 20/19/15
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.34	0.30	0.34



OIL ANALYSIS REPORT









VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	🔺 HEAVY	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	46.25	44.3	43.9
SAMPLE IMAGES		method	limit/base	current	history1	history2

Color



Bottom





Contact/Location: Service Manager - AMAROSOH