

## **OIL ANALYSIS REPORT**

### DANIS IND. CORP. BLDG. LINK-BELT RTC-8065S II J9L1-6881 Component

Front Right Planetary

GEAR OIL SAE 85W140 (--- GAL)





NORMAL

DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Ť

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.


#### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		LBC0000193		
Sample Date		Client Info		05 Jan 2024		
Machine Age	hrs	Client Info		1888		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
		ام م مالح میں			Istatawał	Isistem (O
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	17		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>75	1		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	400	338		
Barium	ppm	ASTM D5185m	200	0		
Molybdenum	ppm	ASTM D5185m	12	0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	12	0		
Calcium	ppm	ASTM D5185m	150	9		
Phosphorus	ppm	ASTM D5185m	1650	1062		
Zinc	ppm	ASTM D5185m	125	0		
Sulfur	ppm	ASTM D5185m	22500	23632		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon		ASTM D5185m	>75	1		
Sodium	ppm	ASTM D5185m	×10	۱ <1		
	ppm		> 20	3		
Potassium	ppm	ASTM D5185m		•		
VISUAL		method	limit/base		history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	LIGHT		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
3:36:06) Rev: 1					Submitted I	Bv: Tanner Wel



# **OIL ANALYSIS REPORT**



Visc @ 40°C cSt ASTM D445 368 242		FLUID PROPERTIES		method limit/base		current	history1	history2
Color no image no image no image Bottom no image no image no image GRAPHS Ferrous Alloys for dramin for drami		Visc @ 40°C	cSt	ASTM D445	368	242		
Bottom no image no image no image CRAPHS Ferrous Alloys 0 0 0 0 0 0 0 0 0 0 0 0 0		SAMPLE IMAGE	ES	method	limit/base	current	history1	history2
Bottom no image no image no image		Color				no image	no image	no image
Ferrous Alloys	Jan5,	Bottom				no image	no image	no image
Non-ferrous Metals		GRAPHS						
	ver	Non-ferrous Met						
		450 - Abnormal	2					
		T						
450 <b>Abnomal</b> 400 <b>Base</b> 300 <b>C</b> 300		Abnormal 200						
450 400 Base 350 250 250					lan5/24			
450 <b>Abnomal</b> 400 <b>Base</b> 300 300		Abnormal			Jan5/24			
Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. Lab Number : U8arCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. Lab Number : 106057029 Unique Number : 10822978 Diagnosed : 11 Jan 2024 Diagnostician : Wes Davis US 432	Sample No. Lab Number Unique Number	: LBC0000193 : 06057029 : 10822978	Recieved Diagnose	l :10. ed :11.	Jan 2024 Jan 2024	3 Colum	2329 Pei	rformance W Columbus, ( US 432

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: