

# **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

### Area SYNOIL 8K FG [156932] Machine Id KAESER 1017 - LIQUIBOX Component

Compressor

#### DIAGNOSIS

## Recommendation

Resample at the next service interval to monitor.

# Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

# Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	<b>ATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UCZ06057422		
Sample Date		Client Info		06 Jan 2024		
Machine Age	hrs	Client Info		73418		
Oil Age	hrs	Client Info		6000		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
				-		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>3	0		
Titanium	ppm	ASTM D5185m	>3	0		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>10	2		
Lead	ppm	ASTM D5185m	>10	0		
Copper	ppm	ASTM D5185m	>50	5		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1	0		
Barium	ppm	ASTM D5185m	0.3	0		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m	0	0		
Magnesium	ppm	ASTM D5185m	0	<1		
Calcium	ppm	ASTM D5185m	0.5	0		
Phosphorus	ppm	ASTM D5185m	536	29		
Zinc	ppm	ASTM D5185m	0.2	0		
Sulfur	ppm	ASTM D5185m	649	14627		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	1		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.337	0.45		



# **OIL ANALYSIS REPORT**

VISUAL





		White Metal	scalar	*Visual	NONE	NONE		
		Yellow Metal	scalar	*Visual	NONE	NONE		
		Precipitate	scalar	*Visual	NONE	NONE		
		Silt	scalar	*Visual	NONE	NONE		
		Debris	scalar	*Visual	NONE	NONE		
		Sand/Dirt	scalar	*Visual	NONE	NONE		
	/24	Appearance	scalar	*Visual	NORML	NORML		
	Jan6/24	Odor	scalar	*Visual	NORML	NORML		
		Emulsified Water	scalar	*Visual	>0.05	NEG		
		Free Water		*Visual	>0.05	NEG		
		FIEE Walei	scalar	VISUAI		NEG		
		FLUID PROPERT	IES	method				history2
		Visc @ 40°C	cSt	ASTM D445	42.0	43.2		
		SAMPLE IMAGES	5	method	limit/base	current	history1	history2
	Jan6/24	Color					no image	no image
		Bottom					no image	no image
	5	6 - nickel						
	шdd	0 - +27 2			Jan6/24			
	ndd	Non-ferrous Metal	s		Jan6,24			
	udd	Non-ferrous Metal	S		Jan6/24			
		Non-ferrous Metal	5		Jan6,24			
	udd	Non-ferrous Metal	S		Jan6/24			
		Non-ferrous Metal	5		Jan6/24			
		Non-ferrous Metal	S					
		Non-ferrous Metal	S					
		Non-ferrous Metal	S		Jan6/24			
		Non-ferrous Metal	5		Jan6/24	Acid Number		
		Non-ferrous Metal	s		Jan6/24			
	mad	Non-ferrous Metal	S		Jan6/24			
	mad	Non-ferrous Metal	S		Jan6/24			
	mad	Non-ferrous Metal	S		Jan6/24			
	mad	Non-ferrous Metal	S		Acid Number (mg KOH(g) Acid Number (mg KOH(g)	50 40 30 20 10 00		
	mad	Non-ferrous Metal	S		Acid Number (mg KOH(g) Acid Number (mg KOH(g)	50 40 30 20 10 00		
Laboratory Sample No. Lab Numbe Unique Numb	und (3-06)-183	Non-ferrous Metal	501 Madis Recieved Diagnose	l :10. ed :12.	Jan6/24 - Jan6/2	50 40 30 10 10 10 10 10 13 20 20 10 10 10 10 10 10 10 10 10 10 10 10 10	COMPRESSO	
Sample No.	uud (2-06) 153 <b>ber</b>	Non-ferrous Metal	601 Madis Recieved	l :10. ed :12.	ry, NC 275 Jan 2024 Jan 2024	50 40 30 10 10 10 10 10 13 20 20 10 10 10 10 10 10 10 10 10 10 10 10 10	227 AMBROSI	<b>R EQUIPMEN</b> O DR, SUITE J GURNEE, I

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: x: