

## **OIL ANALYSIS REPORT**

## NORTH PLANT SULLAIR NP-COMP 01 (S/N 201312030054) Component

Compressor

### **ULTRACHEM PALEXTRA 44 (5 QTS)**

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

#### Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0884872	WC0753861	WC0696323
Sample Date		Client Info		10 Jan 2024	04 Dec 2022	18 May 2022
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ATTENTION	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	7	4	2
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m		<1	<1	<1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>25	2	5	11
Lead	ppm	ASTM D5185m	>25	0	0	<1
Copper	ppm	ASTM D5185m		5	4	4
Tin	ppm		>15	<1	<1	1
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		<1	0	<1
	ppin					
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	2
Barium	ppm	ASTM D5185m	0.3	214	150	187
Molybdenum	ppm	ASTM D5185m	0	<1	0	0
Manganese	ppm	ASTM D5185m	0.3	1	<1	<1
Magnesium	ppm	ASTM D5185m	0.4	4	4	4
Calcium	ppm	ASTM D5185m	0	2	6	3
Phosphorus	ppm	ASTM D5185m	689	17	56	24
Zinc	ppm	ASTM D5185m	0	44	64	45
Sulfur	ppm	ASTM D5185m	1237	223	122	232
CONTAMINANTS	\$	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	4	4	5
Sodium	ppm	ASTM D5185m		147	132	117
Potassium	ppm	ASTM D5185m	>20	4	2	4
Water	%	ASTM D6304	>0.1	NEG	NEG	NEG
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	8278	<b>1</b> 1640	
Particles >6µm		ASTM D7647	>2500	1651	1298	
Particles >14µm		ASTM D7647	>320	154	95	
Particles >21µm		ASTM D7647		35	19	
Particles >38µm		ASTM D7647	>20	1	1	
Particles >71µm		ASTM D7647		0	0	
Oil Cleanliness		ISO 4406 (c)	>20/18/15	20/18/14	▲ 21/17/14	
FLUID DEGRADA	TION_	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.135	0.59	0.38	0.38
ACIU MUMDEL (AN)	niy NOR/9	AG I IVI DOU40	0.155	0.59	0.00	0.00



# **OIL ANALYSIS REPORT**








Ē

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	44.62	41.6	42.5	41.8
SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Color					9	
Bottom						



Contact/Location: TODD PITMAN - LANNEW