

OIL ANALYSIS REPORT

Area PG-46 [SO-271761] Machine Id GARDNER DENVER S121427 - MENASHA GROUP Component

Compressor Fluid

{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





NORMAL

				5002020		
SAMPLE INFORM	ΛΑΤΙΟΝ	method	limit/base	current	history1	history2
Sample Number		Client Info		UFD0000219		
Sample Date		Client Info		09 Dec 2023		
Machine Age	hrs	Client Info		86587		
Oil Age	hrs	Client Info		16606		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	0		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		306		
Zinc	ppm	ASTM D5185m		3		
Sulfur	ppm	ASTM D5185m		0		
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	14		
Sodium	ppm	ASTM D5185m		7		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.53		



OIL ANALYSIS REPORT

VISUAL


bpm


ppm

cSt (40°C)

Laboratory Sample No. Lab Number Unique Number Test Package

Acid Number





VIOUAL		methou			TISLOT Y I	mstoryz
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	LIGHT		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.1	NEG		
Free Water	scalar	*Visual	20.1	NEG		
				NEG		
FLUID PROPERT	FIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		47.1		
SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS			-		2	
6 +			Dec9/23			
Non-ferrous Meta	s					
6						
Dec3/23			Dec9/23			
∝ Viscosity @ 40°C			Q	Acid Number		
5 T			. 0.6			
0 - Abnormal			(B)HO.4 (B)HO.3 (B)HO.3 (B)HO.4 (B)HO.	8 -		
5			Ë 0.3	6 -		
Abaramat			- 0.2	4		
			N 0.1	2		
54						3
Dec9/22			Dec9/23	Dec9/23		Dec3/23
WearCheck USA - 5	501 Madi	son Ave Ca	rv NC 2751	3	FI UID-AII	RE DYNAMICS
	Recieved	d :11.	Jan 2024			0 ALBION AVE
	Diagnos	ed : 14	Jan 2024			AUMBURG, IL
	Diagnosi		n Baldridge			US 60193
IND 2			_			ct: ED DIENER
ntact Customer Serv	ice at 1-8	00-237-1369	9.	ed	.diener@fluidaire	edynamics.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

F:

T: (847)678-8388