


# **OIL ANALYSIS REPORT**

## Sample Rating Trend







# HPU17 Machine Id HTS44 Component

Hydraulic System

ESSO HYJET IV-A PLUS (--- GAL)

$\neg$	1 /		10	0	10
	ΙА		VС		-
	и ч	$\sim$	~		$\cdot$

## Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

The water content is negligible. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Feb2022 Feb2022 Aug/2022 Dec/2022 Feb2023 May/2023 Occ6023 Jan/2024								
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2		
Sample Number		Client Info		WC0896025	WC0817693	WC0778660		
Sample Date		Client Info		09 Jan 2024	16 Oct 2023	08 May 2023		
Machine Age	mths	Client Info		0	0	0		
Oil Age	mths	Client Info		0	0	0		
Oil Changed		Client Info		N/A	N/A	N/A		
Sample Status				NORMAL	NORMAL	ATTENTION		
WEAR METALS		method	limit/base	current	history1	history2		
Iron	ppm	ASTM D5185m	>20	0	0	0		
Chromium	ppm	ASTM D5185m	>20	0	4	5		
Nickel	ppm	ASTM D5185m	>20	0	<1	<1		
Titanium	ppm	ASTM D5185m		0	0	0		
Silver	ppm	ASTM D5185m		0	0	0		
Aluminum	ppm	ASTM D5185m	>20	0	2	0		
Lead	ppm	ASTM D5185m	>20	0	0	0		
Copper	ppm	ASTM D5185m	>20	0	<1	1		
Tin	ppm	ASTM D5185m	>20	<1	0	0		
Vanadium	ppm	ASTM D5185m		0	0	0		
Cadmium	ppm	ASTM D5185m		0	0	<1		
ADDITIVES		method	limit/base	current	history1	history2		
Boron	ppm	ASTM D5185m		<1	2	0		
Barium	ppm	ASTM D5185m		0	0	0		
Molybdenum	ppm	ASTM D5185m		0	0	0		
Manganese	ppm	ASTM D5185m		0	0	0		
Magnesium	ppm	ASTM D5185m		0	1	1		
Calcium	ppm	ASTM D5185m	110	119	119	124		
Phosphorus	ppm	ASTM D5185m	37	30727	41577	10711		
Zinc	ppm	ASTM D5185m		0	0	1		
Sulfur	ppm	ASTM D5185m	220	231	260	325		
CONTAMINANTS		method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>15	0	1	1		
Sodium	ppm	ASTM D5185m		5	5	5		
Potassium	ppm	ASTM D5185m	>20	31	39	37		
Water	%	ASTM D6304	>0.750	0.230	0.661	0.508		
ppm Water	ppm	ASTM D6304	>7500	2300	6610	5083.4		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2		
Particles >4µm		ASTM D7647	>640	412	254	276		
Particles >6µm		ASTM D7647	>160	117	63	127		
Particles >14µm		ASTM D7647	>20	16	13	<b>2</b> 5		
Particles >21µm		ASTM D7647	>4	5	5	<b>6</b>		
Particles >38µm		ASTM D7647	>3	0	0	0		
Particles >71µm		ASTM D7647	>3	0	0	0		
Oil Cleanliness		ISO 4406 (c)	>16/14/11	16/14/11	15/13/11	<b>▲</b> 15/14/12		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2		
Acid Number (AN)	mg KOH/g	ASTM D8045	0.04	0.183	0.186	0.267		



# **OIL ANALYSIS REPORT**



\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F:

T: (478)275-4030