

OIL ANALYSIS REPORT

Sample Rating Trend

ISO



PRECISION EDGE 114

Component

Hydraulic System

{not provided} (--- Oz)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

				Jan 2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC06060204		
Sample Date		Client Info		11 Jan 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	15		
Chromium	ppm	ASTM D5185m	>20	1		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	2		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>20	1		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		2		
Magnesium	ppm	ASTM D5185m		7		
Calcium	ppm	ASTM D5185m		2834		
Phosphorus	ppm	ASTM D5185m		145		
Zinc	ppm	ASTM D5185m		41		
Sulfur	ppm	ASTM D5185m		13416		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	3		
Sodium	ppm	ASTM D5185m		8		
Potassium	ppm	ASTM D5185m	>20	5		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	<u> </u>		
Particles >6µm		ASTM D7647	>1300	13986		
Particles >14µm		ASTM D7647	>160	296		
Particles >21µm		ASTM D7647	>40	43		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	24/21/15		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
A ! N (AA))	1/011/	ACTM DODAE		0.14		


Acid Number (AN) mg

mg KOH/g ASTM D8045

).14



OIL ANALYSIS REPORT







Laboratory Sample No. Lab Number **Unique Number**

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC06060204

: 06060204 : 10831586 Test Package : IND 2

: 12 Jan 2024 Recieved Diagnosed : 16 Jan 2024 : Don Baldridge Diagnostician

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) **BUCKEYE LUBRICANTS**

20801 SALISBURY RD BEDFORD, OH US 44146

Contact: TOM GARGANTA sales@buckeyelubricants.com

T: (216)581-3600 F: (216)581-2734

Contact/Location: TOM GARGANTA - BUCBED