




OIL ANALYSIS REPORT

Sample Rating Trend



DIRT



Machine Id
2158

Component
Hydraulic System

Fluid
TECHNOLUBE LSC 2075TH (2 GAL)

DIAGNOSIS

▲ Recommendation

No corrective action is recommended at this time. Filtration at the time of sampling has been noted. Resample at the next service interval to monitor.

▲ Wear

The copper level is marginal. All other component wear rates are normal.

▲ Contamination

There is a high amount of particulates present in the oil. Elemental level of silicon (Si) above normal.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PH0000350	---	---
Sample Date	Client Info		19 Dec 2023	---	---
Machine Age	mths	Client Info	1	---	---
Oil Age	mths	Client Info	0	---	---
Oil Changed	Client Info		Filtered	---	---
Sample Status			ABNORMAL	---	---

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.05	NEG	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	13	---
Chromium	ppm	ASTM D5185m	>20	0	---
Nickel	ppm	ASTM D5185m	>20	1	---
Titanium	ppm	ASTM D5185m		0	---
Silver	ppm	ASTM D5185m		0	---
Aluminum	ppm	ASTM D5185m	>20	2	---
Lead	ppm	ASTM D5185m	>20	<1	---
Copper	ppm	ASTM D5185m	>20	▲ 21	---
Tin	ppm	ASTM D5185m	>20	0	---
Vanadium	ppm	ASTM D5185m		0	---
Cadmium	ppm	ASTM D5185m		0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	---
Barium	ppm	ASTM D5185m		0	---
Molybdenum	ppm	ASTM D5185m		0	---
Manganese	ppm	ASTM D5185m		2	---
Magnesium	ppm	ASTM D5185m		0	---
Calcium	ppm	ASTM D5185m		0	---
Phosphorus	ppm	ASTM D5185m		101	---
Zinc	ppm	ASTM D5185m		32	---
Sulfur	ppm	ASTM D5185m		100	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	▲ 30	---
Sodium	ppm	ASTM D5185m		16	---
Potassium	ppm	ASTM D5185m	>20	0	---


FLUID CLEANLINESS

	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	>2500	▲ 151668	---	---
Particles >6µm	ASTM D7647	>640	▲ 84012	---	---
Particles >14µm	ASTM D7647	>80	▲ 7060	---	---
Particles >21µm	ASTM D7647	>20	▲ 1428	---	---
Particles >38µm	ASTM D7647	>4	▲ 30	---	---
Particles >71µm	ASTM D7647	>3	1	---	---
Oil Cleanliness	ISO 4406 (c)	>18/16/13	▲ 24/24/20	---	---

FLUID DEGRADATION






	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.088	---

Particle Filter (Magn: 200 x)





OIL ANALYSIS REPORT



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PH0000350 **Received** : 16 Jan 2024
Lab Number : 06061036 **Diagnosed** : 23 Jan 2024
Unique Number : 10832418 **Diagnostician** : Doug Bogart
Test Package : PLANT (Additional Tests: PrtFilter)

ATLANTIC HYDRAULIC SYSTEMS
 90 PRECISION DR
 SHIRLEY, NY
 US 11967
 Contact: Lisa Wendt
 lwendt@atlantichydraulicsystems.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.05	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	31.9	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image
PrtFilter				no image	no image

GRAPHS

