


OIL ANALYSIS REPORT

Sample Rating Trend



ISO



Machine Id
PRESS 8.5 (S/N 260610)

Component
Hydraulic System

Fluid
ESSO NUTO H ISO 46 (--- LTR)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. We recommend an early resample to monitor this condition. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The water content is negligible.

Fluid Condition

The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	RP0034646	RP0007364	RP99310
Sample Date	Client Info	15 Jan 2024	18 Jan 2021	09 Sep 2018
Machine Age	yrs Client Info	0	0	0
Oil Age	yrs Client Info	0	0	0
Oil Changed	Client Info	N/A	N/A	N/A
Sample Status		ABNORMAL	NORMAL	ABNORMAL

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >20	1	<1	2
Chromium	ppm ASTM D5185m >20	0	0	0
Nickel	ppm ASTM D5185m >20	0	1	0
Titanium	ppm ASTM D5185m	0	0	0
Silver	ppm ASTM D5185m	0	0	0
Aluminum	ppm ASTM D5185m >20	0	<1	0
Lead	ppm ASTM D5185m >20	0	<1	<1
Copper	ppm ASTM D5185m >20	3	<1	3
Tin	ppm ASTM D5185m >20	1	0	<1
Antimony	ppm ASTM D5185m	---	0	0
Vanadium	ppm ASTM D5185m	<1	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	0	0	0
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 0	0	0	<1
Manganese	ppm ASTM D5185m	0	0	<1
Magnesium	ppm ASTM D5185m 5	0	2	<1
Calcium	ppm ASTM D5185m 50	34	22	44
Phosphorus	ppm ASTM D5185m 330	328	369	331
Zinc	ppm ASTM D5185m 410	376	452	414

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >15	0	<1	<1
Sodium	ppm ASTM D5185m	2	0	0
Potassium	ppm ASTM D5185m >20	0	0	1
Water	% ASTM D6304 >0.05	0.008	0.003	0.019
ppm Water	ppm ASTM D6304 >500	90	37.9	190

FLUID CLEANLINESS


method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647 >5000	▲ 11313	1177	▲ 30370
Particles >6µm	ASTM D7647 >1300	1071	324	▲ 8804
Particles >14µm	ASTM D7647 >160	47	33	▲ 1044
Particles >21µm	ASTM D7647 >40	10	10	▲ 268
Particles >38µm	ASTM D7647 >10	0	2	8
Particles >71µm	ASTM D7647 >3	0	0	0
Oil Cleanliness	ISO 4406 (c) >19/17/14	▲ 21/17/13	17/16/12	▲ 22/20/17

FLUID DEGRADATION


method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g ASTM D8045 0.45	0.38	0.418	0.325

OIL ANALYSIS REPORT


▲ Particle Trend




Water (KF)




Acid Number



Water (KF)



Viscosity @ 40°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445 46	43.4	44.3	44.6

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------


Color

Bottom




GRAPHS


Ferrous Alloys




Non-ferrous Metals




Viscosity @ 40°C



▲ Particle Count



Acid Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RP0034646 **Recieved** : 16 Jan 2024
Lab Number : 06061094 **Diagnosed** : 17 Jan 2024
Unique Number : 10832476 **Diagnostician** : Wes Davis
Test Package : IND 2

YANFENG - ROMULUS
 9800 INKSTER RD
 ROMULUS, MI
 US 48174
 Contact: AARON BLIESNER
 aaron.bliesner@yanfeng.com
 T:
 F: (734)946-0237

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)