

OIL ANALYSIS REPORT

Area ULTRA COOLANT [57945] Machine Id INGERSOLL RAND VN1679U14104 - HEIDTMAN STEEL Component

Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL


			12 . 14 /1			
SAMPLE INFORM	/IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06061310		
Sample Date		Client Info		02 Jan 2024		
Machine Age	hrs	Client Info		61065		
Oil Age	hrs	Client Info		5174		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0		
Barium	ppm	ASTM D5185m	500	802		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	0	0		
Calcium	ppm	ASTM D5185m	0	3		
Phosphorus	ppm	ASTM D5185m	20	36		
Zinc	ppm	ASTM D5185m	0	70		
Sulfur	ppm	ASTM D5185m	200	301		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		35		
Potassium	ppm	ASTM D5185m	>20	4		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.28		



OIL ANALYSIS REPORT

VISUAL





	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	LIGHT		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
/24		scalar	*Visual	NORML	NORML		
Jan 2,224	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
	Free Water			20.1	NEG		
		scalar	*Visual		NEG		
	FLUID PROPER	RTIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	49.4	52.2		
	SAMPLE IMAGE	ES	method	limit/base	current	history1	history2
Jan 2/34 +	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Met	als		Jan224			
	Viscosity @ 40°C	2		Paulo 2.50 (0, 1, 1, 2, 50 (0, 1, 1, 50 (0, 1, 1, 50) (0, 1, 1, 50) (0, 1, 1, 50) (0, 1, 1, 50) (0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,	Acid Number		
Laboratory Sample No. Lab Number	: WearCheck USA - UCH06061310 : 06061310	- 501 Madia Recieved Diagnos	d :16.	Jan2/24	Jan2/24	HENRY FOST 4700 LEBOUF SAI	
Grante 12367 Unique Number Grante 12367 Test Package discuss this sample report, Denotes test methods that	e : IND 2 , contact Customer Ser		800-237-1369		Cor		US 6313 VON HATTE atten@jhf.co (314)593-126

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Ĵ,

Contact/Location: RACHEL VON HATTEN - UCJOHSAI

F: (314)874-0965