

OIL ANALYSIS REPORT

ULTRA COOLANT **INGERSOLL RAND CBV519632 - TEAM THREE GROUP** Component

Compressor

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend





SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH0000529	UCH05889192	
Sample Date		Client Info		03 Jan 2024	19 Jun 2023	
Machine Age	hrs	Client Info		7345	7328	
Oil Age	hrs	Client Info		26	5839	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	
Chromium	ppm	ASTM D5185m	>10	<1	0	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		<1	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>25	2	0	
Lead	ppm	ASTM D5185m	>25	0	0	
Copper	ppm	ASTM D5185m	>50	<1	<1	
Tin	ppm	ASTM D5185m	>15	<1	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	50	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	<1	
Magnesium	ppm	ASTM D5185m		1	<1	
Calcium	ppm	ASTM D5185m		94	52	
Phosphorus	ppm	ASTM D5185m		552	335	
Zinc	ppm	ASTM D5185m		0	3	
Sulfur	ppm	ASTM D5185m		918	629	
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	
Sodium	ppm	ASTM D5185m		8	15	
Potassium	ppm	ASTM D5185m	>20	1	2	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.21	0.16	



OIL ANALYSIS REPORT

VISUAL





THE LABORATORY	Laboratory Sample No. Lab Number Unique Number Test Package	: (06061313	son Ave., Ca d : 16 c ed : 17 c ician : Dor		JOHN HENRY FOSTER COMPANY 4700 LEBOURGET STREET SAINT LOUIS, MO US 63134 Contact: RACHEL VON HATTEN rvonhatten@jhf.com T: (314)593-1267 GM 106:2012) F: (314)874-0965			
		60 (2-0+) 50 40	Viscosity @ 40°C			Jan3/24 (0.25 9.0.0 Minuber (mg K0H(g)) Acid Number (mg K0H(g)) Acid Number (mg K0H(g))	Acid Number		- 42/5 ref
		10 8 4 2	Non-ferrous Meta	ls		Jan3/24			
		10 8 4 2 0	GRAPHS Ferrous Alloys			24			
		E	Bottom						no image
	Jan3/24		Color						no image
			/isc @ 40°C SAMPLE IMAGE	cSt	ASTM D445 method	46.0 limit/base	49.8 current	49.9 history1	 history2
			FLUID PROPER	TIES	method	limit/base	current	history1	history2
			Free Water	scalar scalar	*Visual	>0.1	NEG	NEG	
	را م		Ddor Emulsified Water	scalar	*Visual *Visual	NORML >0.1	NORML NEG	NORML NEG	
	Jan3/24		Appearance	scalar	*Visual	NORML	NORML	NORML	
			Debris Sand/Dirt	scalar scalar	*Visual *Visual	NONE	NONE NONE	NONE	
			Silt	scalar	*Visual	NONE	NONE	NONE	
			Precipitate	scalar	*Visual	NONE	NONE	NONE	
		1	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	

Submitted By: RACHEL VON HATTEN