

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



North Plant-Purification Machine Id CS32215A

Component

Lube System

HIGH PERFORMANCE LUBRICANTS TURBINE LIFE 46 (16 GAL

HIGH PERFORMANCE LODRICANTS TURBINE LIFE 40 (10 GAI

DIAGNOSIS Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

BINE LIFE 46 (1	6 GAL)	10 p 2018 Feb 20	19 Jun2019 Dec2019 O	et2020 Jun2021 Mar2022 Jan20	23 Sep2023	
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0870645	WC0850031	WC0804732
Sample Date		Client Info		10 Jan 2024	14 Sep 2023	23 Jun 2023
Machine Age	mths	Client Info		0	0	0
Oil Age	mths	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	4	4	3
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	2	0	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>75	2	2	2
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	<1
Molybdenum	ppm	ASTM D5185m		<1	0	<1
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		2	4	9
Calcium	ppm	ASTM D5185m		3	5	4
Phosphorus	ppm	ASTM D5185m		142	127	139
Zinc	ppm	ASTM D5185m		0	1	10
Sulfur	ppm	ASTM D5185m		19367	20853	20175
CONTAMINANT	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	0	<1	<1
Sodium	ppm	ASTM D5185m		3	9	6
Potassium	ppm	ASTM D5185m	>20	1	0	2
Water	%	ASTM D6304	>0.1	0.003	0.005	0.006
ppm Water	ppm	ASTM D6304	>1000	26	53.3	60.8
FLUID CLEANL	INESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>640	161	280	<u></u> 5912
Particles >6µm		ASTM D7647	>160	62	120	<u></u> 1470
Particles >14μm		ASTM D7647	>40	12	17	37
Particles >21µm		ASTM D7647	>10	3	6	2
Particles >38µm		ASTM D7647	>3	0	0	0
Particles >71µm		ASTM D7647	>3	0	0	0

ISO 4406 (c) >16/14/12

mg KOH/g ASTM D8045 0.19

15/13/11

0.32

Oil Cleanliness

Acid Number (AN)

FLUID DEGRADATION

15/14/11

0.32

20/18/12

0.41



OIL ANALYSIS REPORT



* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F:

T: (641)295-0086