


OIL ANALYSIS REPORT

Fermentation

Lightnin FFG39MB01 Main Fermentor, Agitator

Gearbox

JAX FGG-AW ISO 220 (28 GAL)





Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the component. The amount and size of particulates present in the system is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		ul2019 Ma	r2020 Jan2021 Oct2	021 Jul2022 Jan2023 A	lug2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0857616	WC0819245	WC0808212
Sample Date		Client Info		11 Jan 2024	17 Oct 2023	08 Aug 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	1	1	6
Chromium	ppm	ASTM D5185m	>15	<1	0	0
Nickel	ppm	ASTM D5185m	>15	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	0	1
Lead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m	>200	<1	0	<1
Tin	ppm	ASTM D5185m	>25	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		<1	0	<1
Phosphorus	ppm	ASTM D5185m		449	488	491
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		604	618	727
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon		ASTM D5185m	>50	0	0	<1
Sodium	ppm	ASTM D5185m	>50	0	0	<1
Potassium	ppm	ASTM D5185m	>20	1	0	0
Water	%	ASTM D6304	>0.2	0.003	0.005	0.001
ppm Water	ppm	ASTM D6304	>2000	31	51.8	6.6
FLUID CLEANLIN		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	8346	11626	18484
Particles >6μm		ASTM D7647		688	1042	1604
Particles >14µm		ASTM D7647	>640	25	43	57
Particles >14µm		ASTM D7647		6	7	14
Particles >38µm		ASTM D7647	>40	0	0	0
Particles >71µm		ASTM D7647		0	0	0
Oil Cleanliness		ISO 4406 (c)	>21/19/16	20/17/12	21/17/13	21/18/13
FLUID DEGRADA	TION _	method	limit/base	current	history1	history2
			— IIIIIII Dasc		•	
Acid Number (AN)	mg KOH/g	ASTM D8045		0.31	0.31	0.31



OIL ANALYSIS REPORT

